

**Miele**



PDR 908 [EL MAR 3N AC 400V 50/60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 8.0 kg.



- Drum volume 130 l, load capacity 8.0kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516218463 / Article number : 52908482MAR / Material number: 11251050

<b>Construction type and version</b>	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Stainless steel
Maximum load size in kg	8.0
Drum volume in l	130
Drying system	Vented
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	5.5
Specific energy consumption in kWh/kg	0.50
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kWh/kg	0.50
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in kWh/kg	0.42
Programme duration in min.	42
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	42
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	37
<b>Controls</b>	
Control system	M Touch Flex
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3N~ 400V 50/60HZ
Electric heater rating in kW	6.14
Total connected load in kW	6.40
Fuse rating in A	10

PDR 908 [EL MAR 3N AC 400V 50/60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 8.0 kg.



<b>Possible voltage variant 1</b>	
Electrical connection	230V~ 50/60HZ
Electric heater rating in kW	2.9
Total connected load in kW	3.24
Fuse rating in A	16
<b>Possible voltage variant 2</b>	
Electrical connection	3~ 230V 50/60HZ
Electric heater rating in kW	6.1
Total connected load in kW	6.40
Fuse rating in A	16
<b>Dimensions and weight</b>	
External dimensions, net height in mm	850
External dimensions, net width in mm	605
External dimensions, net depth in mm	717
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	52
Gross weight in kg	57
Maximum floor loading in N	920
<b>Emissions data</b>	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.76
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	95
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•

PDR 908 [EL MAR 3N AC 400V 50/60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 8.0 kg.



Standards, test certificates and symbols	
CE	•
Splash-proof safety rating IPX4	•
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.