

Miele



PDR 908 HP [EL MAR 2 AC 208/240V 60Hz]

Heat-pump dryers

Lloyd's Register approved, load size 8.0 kg.



- Drum volume 130 l, load capacity 8.0kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516218807 / Article number : 52908289MAR / Material number: 11251250

| Construction type and version | |
|--|------------------------------|
| Construction type | Front-loader, stackable |
| Range | Performance Plus |
| Front | Stainless steel |
| Maximum load size in kg | 8.0 |
| Drum volume in l | 130 |
| Drying system | Heat pump |
| Door opening [Ø] in mm | 370 |
| Door opening angle in degrees | 167 |
| Door hinge | left |
| Stainless steel honeycomb drum | • |
| Application | |
| Suitable for offshore use | • |
| Suitable for marine use | • |
| Performance data | |
| Maximum evaporation capacity in l/hour | 2.6 |
| Specific energy consumption in kWh/kg | 0.20 |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kWh/kg | 0.20 |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in kWh/kg | 0.17 |
| Programme duration in min. | 88 |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes | 88 |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes | 76 |
| Controls | |
| Control system | M Touch Flex |
| Programmability | programmable |
| User interface | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Language can be selected easily at any time | • |
| Standard electrical connection | |
| Heating type | Heat pump |
| Electrical connection | 2~ 208-240V 60HZ |
| Total connected load in kW | 1.20 |
| Fuse rating in A | 15 |

PDR 908 HP [EL MAR 2 AC 208/240V 60Hz]

Heat-pump dryers

Lloyd's Register approved, load size 8.0 kg.



| Dimensions and weight | |
|--|---------------------|
| External dimensions, net height in mm | 850 |
| External dimensions, net width in mm | 605 |
| External dimensions, net depth in mm | 777 |
| External dimensions, gross height in mm | 940 |
| External dimensions, gross width in mm | 660 |
| External dimensions, gross depth in mm | 820 |
| Net weight in kg | 72 |
| Gross weight in kg | 78 |
| Maximum floor loading in N | 920 |
| Emissions data | |
| Emissions – sound pressure at workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 3.60 |
| Features | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Fluff filter in the door | • |
| Low-maintenance heat exchanger filter system | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Gentle tumble function | • |
| Condensed water drainage | • |
| Communication slot | • |
| Drying basket (optional) | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| Efficiency and sustainability | |
| Recycling rate in % | 95 |
| Contains fluorinated greenhouse gases | • |
| Hermetically sealed system | • |
| Coolant | R134a |
| Refrigerant quantity in kg | 0.59 |
| Refrigerant global warming potential in kg CO ₂ e | 1,430 |
| Appliance global warming potential in kg CO ₂ e | 844 |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| LAN/WiFi module (optional) | • |
| Standards, test certificates and symbols | |
| WEEE | • |
| Lloyd's Register | • |
| Complies with Machinery Directive 2006/42/EC | • |

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment.
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.