

Miele

The world
of Miele Marine



PDR 922 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

- Drum volume 400 l 400 l, load capacity 22 kg
- Unique, gentle fabric care – honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load in kg	22
Load size with a load ratio of 1:23	16
Load size with a load ratio of 1:18	22
Load ratio	1:18
Drum volume in l	400
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Maximum evaporation capacity in l/hour	22.3
Specific energy consumption in kWh/kg	0.5
Programme duration in min.	23
Tested operating hours	20000
Controls	
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	3 AC 400V 50/60HZ
Electric heater rating in kW	22.5
Total connected load in kW	23.5
Fuse rating in A	50

PDR 922 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

Dimensions and weight	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	198.9
Gross weight in kg	213
Emissions data	
Heat dissipation into the room in MJ/h	2.6
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling Flex	•
Communication slot	•
	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•
Capacities	
Respirator masks [number]	16
Overalls [number]	3
Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	4
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	391
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	3

PDR 922 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

Test certificate	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•

Miele

Miele & Cie. KG

Carl-Miele-Straße 29
33332 Gütersloh
Germany
Tel. +49 5241 89-0
www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376
Australia, Asia, Oceania: +61 3 9764 7880
Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com