

**Miele**



PG 8060 [OFFSHORE 3 AC 220V 60Hz 20A 6,5kW]

Freestanding fresh water dishwasher  
with baskets, for offshore locations such as drilling platforms.



- Max. cleaning performance\*: 76 plates/h
- First-class results thanks to freshwater wash system
- Special electrical connection for specific site conditions
- Extremely hygienic results –final rinse temperature of 85°C
- Versatile processing of 2 wire baskets per cycle

EAN: 4002515524428 / Article number : 61806005N / Material number: 09736630

<b>Construction type and version</b>	
Construction type	Freestanding dishwasher
Range	Professional
Wash system	Fresh water
Number of levels	2
Front	Stainless steel
Lid	Stainless steel
Side panels	Stainless steel
Drying	AutoOpen assisted drying
<b>Application</b>	
Suitable for offshore and marine services	•
<b>Performance data</b>	
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	28
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	76
Cleaning performance, baskets/h	2
Service life in wash cycles	15,000
<b>Controls</b>	
Control system	TouchControl
Programme selection	Touch on Metal
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Language-neutral operation	•
<b>Standard electrical connection</b>	
Electrical connection	3 AC 220V 60HZ
Heater rating in kW	6.10
Total connected load in kW	6.50
Fuse rating in A	20
Length of mains connection cable in m	1.70
<b>Possible voltage variant 1</b>	
Electrical connection	AC 220V 60HZ
Heater rating in kW	2.3
Total connected load in kW	2.70
Fuse rating in A	16

PG 8060 [OFFSHORE 3 AC 220V 60Hz 20A 6,5kW]

Freestanding fresh water dishwasher  
with baskets, for offshore locations such as drilling platforms.



<b>Water connection/drainage</b>	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	1,00-10,00
Drain pump [DN]	22
Maximum delivery head for drain pump in cm	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.70
Water protection system	Waterproof system
Water consumption per wash cycle in l	8.00
<b>Dimensions and weight</b>	
External dimensions, net height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	600
External dimensions, net depth in mm	600
External dimensions, gross height in mm	950
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	690
Usable space in wash cabinet, height in mm	520
Usable space in wash cabinet, width in mm	530
Usable space in wash cabinet, depth of upper basket in mm	474
Usable space in wash cabinet, depth of lower basket in mm	505
In-feed height above floor in mm	216
Net weight in kg	72
Gross weight in kg	84
Maximum floor loading in N	1,200
<b>Emissions data</b>	
Emissions – sound pressure at workplace (LpA)	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57.0
Heat dissipation into the room in MJ/h	1.08
<b>Programmes</b>	
Universal	•
Short	•
Cold/Pre-wash	•
Glasses	•
Cutlery	•
Intensive	•
Reactivation	•
Drainage by pump	•

PG 8060 [OFFSHORE 3 AC 220V 60Hz 20A 6,5kW]

Freestanding fresh water dishwasher  
with baskets, for offshore locations such as drilling platforms.



<b>Basket design</b>	
1 x O 891 upper basket for cups	•
1 x U 890 lower basket for inserts	•
1 x E 810 insert for dessert plates	•
2 x E 816 inserts for plates	•
2 x E 165 inserts for cutlery	•
Height-adjustable upper basket	•
<b>Features</b>	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
In-door salt container	•
AutoOpen assisted drying	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•
Adjustable rinse time	•
Optical interface	•
A wide range of accessories (optional)	•
<b>Connection options</b>	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
<b>Standards, test certificates and symbols</b>	
CE	•
Complies with Machinery Directive 2006/42/EC	•
EMC	•
Interference suppression	•
VDE	•
DIN 10512	•
EN 1717	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.