

Miele

The world
of Miele Marine



PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Construction type and design	
Construction type	Built-under dishwasher
Range	Professional
Wash system	Fresh water
Number of levels	2
Front	Stainless steel
Side panels	Stainless steel
Convertible to a freestanding appliance	Stand 1-80, stainless steel
Drying	AutoOpen assisted drying
Application	
Suitable for offshore and marine services	•
Performance data	
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	15
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	152
Cleaning performance, baskets/h	8
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	15000
Controls	
Control system	TouchControl
Programme selection	Touch on Metal
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	2 PH. 240V 60HZ
Heater rating in kW	5.4
Total connected load in kW	5.8
Fuse rating in A	30
Length of mains connection cable in m	2.2
Possible voltage variant 1	
Electrical connection	3 PH. 240V 60HZ
Heater rating in kW	5.4
Total connected load in kW	5.8
Fuse rating in A	20

- Max. cleaning performance*: 152 plates/h
- Extremely hygienic results – final rinse temperature 85 °C °C
- Simple to operate thanks to clear fascia panel design
- First-class results thanks to freshwater wash system
- Always the right programme - item-specific solutions

PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	1-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Dimensions and weight	
External dimensions, height in mm	820
External dimensions, net width in mm	530
External dimensions, net depth in mm	505
External dimensions, gross height in mm	940
External dimensions, gross width in mm	675
External dimensions, gross depth in mm	685
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	530
Usable space in wash cabinet, depth of upper baske	474
Usable space in wash cabinet, depth of lower basket in mm	505
In-feed height above floor in mm	216
Net weight [kg]	63
Gross weight in kg	69
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57
Heat dissipation into the room in MJ/h	1.08
Programmes	
Universal	•
Short	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
1 x O 891 upper basket for cups	•
1 x U 890 lower basket for inserts	•
1 x E 810 insert for dessert plates	•
2 x E 816 inserts for plates	•
2 x E 165 inserts for cutlery	•
Height-adjustable upper basket	•

PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Features	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
AutoOpen drying	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Adjustable temperature and temperature holding times	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•
Adjustable rinse time	•
Optical interface	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Test certificate	
CE	•
Complies with Machinery Directive 2006/42/EC	•
EMC	•
Interference suppression	•
VDE	•
EN 1717	•
Lloyd's Register	•

PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Construction type and design	
Construction type	Built-under dishwasher
Range	Professional
Wash system	Fresh water
Number of levels	2
Front	Stainless steel
Side panels	Stainless steel
Convertible to a freestanding appliance	Stand 1-80, stainless steel
Drying	AutoOpen assisted drying
Application	
Suitable for offshore and marine services	•
Performance data	
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	15
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	152
Cleaning performance, baskets/h	8
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	15000
Controls	
Control system	TouchControl
Programme selection	Touch on Metal
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	2 PH. 240V 60HZ
Heater rating in kW	5.4
Total connected load in kW	5.8
Fuse rating in A	30
Length of mains connection cable in m	2.2
Possible voltage variant 1	
Electrical connection	3 PH. 240V 60HZ
Heater rating in kW	5.4
Total connected load in kW	5.8
Fuse rating in A	20

- Max. cleaning performance*: 152 plates/h
- Extremely hygienic results – final rinse temperature 85 °C °C
- Simple to operate thanks to clear fascia panel design
- First-class results thanks to freshwater wash system
- Always the right programme - item-specific solutions

PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	1-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Dimensions and weight	
External dimensions, height in mm	820
External dimensions, net width in mm	530
External dimensions, net depth in mm	505
External dimensions, gross height in mm	940
External dimensions, gross width in mm	675
External dimensions, gross depth in mm	685
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	530
Usable space in wash cabinet, depth of upper baske	474
Usable space in wash cabinet, depth of lower basket in mm	505
In-feed height above floor in mm	216
Net weight [kg]	63
Gross weight in kg	69
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57
Heat dissipation into the room in MJ/h	1.08
Programmes	
Universal	•
Short	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
1 x O 891 upper basket for cups	•
1 x U 890 lower basket for inserts	•
1 x E 810 insert for dessert plates	•
2 x E 816 inserts for plates	•
2 x E 165 inserts for cutlery	•
Height-adjustable upper basket	•

PG 8061 U [HYGIENE MAR]

Built-under fresh-water dishwasher
with baskets approved by Lloyd's Register.

Features	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
In-door salt container	•
AutoOpen drying	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Adjustable temperature and temperature holding times	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•
Adjustable rinse time	•
Optical interface	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Test certificate	
CE	•
Complies with Machinery Directive 2006/42/EC	•
EMC	•
Interference suppression	•
VDE	•
EN 1717	•
Lloyd's Register	•

Miele

Miele & Cie. KG

Carl-Miele-Straße 29
33332 Gütersloh
Germany
Tel. +49 5241 89-0
www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376
Australia, Asia, Oceania: +61 3 9764 7880
Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com