

Miele

My Brochure



PW 5105 Vario [EL LP MAR 3 AC 440V 60Hz]

Washing machine, electrically heated

Special voltage for offshore and marine use, equipped with drain pump.



- Drum volume 100l, load capacity 10,0kg
- Large programme variety - application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient - low water and energy consumption
- Perfect spinning results – residual moisture 50 %[†], g factor 370

EAN : 4002514906324 / Article no. : 51510525MAR / Mat. no. : 07899220

Construction type and version	
Construction type	Front loader
Range	OctoPlus
Front	Octoblue
Load ratio	1:10
Load in kg	10,0
Drum volume in l	100
Door opening [Ø] in mm	370
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Specific water consumption for hot water connection in l/kg	8,00
Specific energy consumption for hot water connection in kWh/kg	0,06
Programme duration in minutes with cold water connection	58
Programme duration in minutes with cold water and hot water connection	53
Residual moisture with cold rinse in %	54
Residual moisture with hot rinse in %	50
Spin speed in rpm	1.100
g factor	370
Tested operating hours	30.000
Controls	
Control system	Profitronic L Vario
Programmability	programmable
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•

PW 5105 Vario [EL LP MAR 3 AC 440V 60Hz]

Washing machine, electrically heated

Special voltage for offshore and marine use, equipped with drain pump.



Standard electrical connection	
Heating type	Electrical
Electrical connection	3 AC 440V 60HZ
Heater rating in kW	7,70
Total connected load in kW	7,90
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Grey water (optional) [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22
Dimensions and weight	
External dimensions, net height in mm	1.020
External dimensions, net width in mm	700
External dimensions, net depth in mm	827
External dimensions, gross height in mm	1.215
External dimensions, gross width in mm	760
External dimensions, gross depth in mm	915
Net weight in kg	148,0
Gross weight in kg	159
Maximum floor loading in N	2750
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2,80
Features	
Imbalance monitoring	•
Disinfection rinse	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
Communication slot	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak load cut-out/energy management (optional)	•

PW 5105 Vario [EL LP MAR 3 AC 440V 60Hz]

Washing machine, electrically heated

Special voltage for offshore and marine use, equipped with drain pump.



Capacities	
Respirator masks [number]	7
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Standards, test certificates and symbols	
CE	•
VDE	•
Splash protection IPX4	•
WEEE	•
RCM	•
Complies with Machinery Directive 2006/42/EC	•

Miele

Miele Appliances Ltd.

Showroom 1

Eiffel 1 Building

Sheikh Zayed Road, Umm Al Sheif

P.O. Box 114782 - Dubai

United Arab Emirates

Tel +971 4 3044 999

Fax +971 4 3418 852

800-MIELE (64353)

E-Mail: info@miele.ae

www.miele.ae/professional