The world of Miele Marine





Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

dispenser module.	
Model and design	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Load ratio	1:10
Load in kg	24
Drum volume in I	240
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Patented honeycomb drum	•
Application	
Suitable for marine use	•
Performance data	
Specific water consumption for cold water connection in I/kg	9
Specific water consumption for hot water connection in Vkg	8.8
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Spin speed in rpm	1100
g factor	541
Tested operating hours	30000
Controls	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard and target group Programmes	
Basic programmes	
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	
Programmes for facility management	
Programmes for dry cleaners	
Programmes for small businesses	<u>•</u>
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for hospitals	•
Programmes for sports clubs	•

- Drum volume 240 I, load capacity 24 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 % %*, g factor541 I

Programmes for beauty clinics, spas, and fitness studios



Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

disperiser module.	
Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module	
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
Standard electrical connection	
Heating type	Indirect steam
Electrical connection	3 AC 400V 60 HZ
Heater rating in kW	
Steam heater rating in kW	50
Total connected load in kW	4.3
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water [number]	2x 1/2" w/ 3/4" threaded union
Dump valve	DN 70
Steam connection	
NEMA Plug: Twist Lock L6-30	2 x ½"
Dimensions and weight	
External dimensions, height in mm	1643
External dimensions, width in mm	1089
External dimensions, depth in mm	1250
External dimensions, gross height in mm	1700
External dimensions, gross width in mm	1336
External dimensions, gross depth in mm	1530
Net weight in kg	650
Gross weight in kg	701
Emissions data	
Emission sound pressure level in the workplace	78 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	4.7
Features	
Patented pre-spin	
Cloth reprocessing	
Imbalance monitoring	<u>•</u>
Temperature monitoring	<u> </u>
Special heater element	
Automatic load control+	•
Volumetric flow meter (optional)	<u>•</u>
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•



Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

aleperieer medalet	
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	<u> </u>
Optical interface for service access	<u> </u>
Serial interface module RS 232 (optional)	•
Peak load cut-out/energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	19
Overalls [number]	4
Over jackets [number]	6
Chemical protection suits [number]	4
Synthetic duvets [number]	3
Synthetic pillows [number]	6
Down duvets [number]	3
Down pillows [number]	6
Cloths, 22 g [number]	546
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	109
Microfibre mops, 40 cm / 120 g [number]	200
Microfibre mops, 50 cm / 170 g [number]	141
Summer horse blankets [number]	4
Test certificate	
CE	<u>•</u>
VDE	<u> </u>
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•



Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

dispenser module.	
Model and design	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Load ratio	1:10
Load in kg	24
Drum volume in I	240
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Patented honeycomb drum	•
Application	
Suitable for marine use	•
Performance data	
Specific water consumption for cold water connection in I/kg	9
Specific water consumption for hot water connection in Vkg	8.8
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Spin speed in rpm	1100
g factor	541
Tested operating hours	30000
Controls	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard and target group Programmes	
Basic programmes	
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	
Programmes for facility management	
Programmes for dry cleaners	
Programmes for small businesses	<u>•</u>
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for hospitals	•
Programmes for sports clubs	•

- Drum volume 240 I, load capacity 24 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 % %*, g factor541 I

Programmes for beauty clinics, spas, and fitness studios



Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module	
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
Standard electrical connection	
Heating type	Indirect steam
Electrical connection	3 AC 400V 60 HZ
Heater rating in kW	0
Steam heater rating in kW	50
Total connected load in kW	4.3
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water [number]	2x 1/2" w/ 3/4" threaded union
Dump valve	DN 70
Steam connection	
NEMA Plug: Twist Lock L6-30	2 x ½"
Dimensions and weight	
External dimensions, height in mm	1643
External dimensions, width in mm	1089
External dimensions, depth in mm	1250
External dimensions, gross height in mm	1700
External dimensions, gross width in mm	1336
External dimensions, gross depth in mm	1530
Net weight in kg	650
Gross weight in kg	701
Emissions data	
Emission sound pressure level in the workplace	78 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	4.7
Features	
Patented pre-spin	
Cloth reprocessing	
Imbalance monitoring	
Temperature monitoring	
Special heater element	
Automatic load control+	
Volumetric flow meter (optional)	
Communication slot	<u>•</u>
Emergency switch-off	<u>•</u>
Machine-independent accessories	•



Washing machine, steam heated (indirect) for marine requirements with liquid dispenser module.

alepender medaler	
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	
Optical interface for service access	<u> </u>
Serial interface module RS 232 (optional)	<u> </u>
Peak load cut-out/energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	19
Overalls [number]	4
Over jackets [number]	6
Chemical protection suits [number]	4
Synthetic duvets [number]	3
Synthetic pillows [number]	6
Down duvets [number]	3
Down pillows [number]	6
Cloths, 22 g [number]	546
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	109
Microfibre mops, 40 cm / 120 g [number]	200
Microfibre mops, 50 cm / 170 g [number]	141
Summer horse blankets [number]	4
Test certificate	
CE	<u> </u>
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•



Miele & Cie. KG

Carl-Miele-Straße 29 33332 Gütersloh Germany Tel. +49 5241 89-0 www.miele marine.com

International Service Contacts

Americas: +1 609419 4376 Australia, Asia, Oceania: +61 3 9764 7880 Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com