



#### Product Features

APL house connection box, surface mounting, lockable, with 12 x LC-D - couplings (SM/APC)

- well organized and tidy entry of Micro pipe systems
- hinges splice cassette (the bending radius is maintained when opened)
- clear fibre - and splice management in splice cassette
- splice cassette for holding 24 pigtails
- integrated comb for holding crimp splices
- ready to splice with exposed and inserted pigtails incl. 12 x LC-D- ceramic couplings green
- LC-fibre pigtails E9/125 µm, 2 m, SM OS2 APC, grade B1, G657.A
- with test protocol for all fibres incl. serial number
- 12 drop-cable entries (3mm Ø) at the bottom of the housing
- 2 cable entries (M20) at the bottom of the housing
- optional Cable entry at the top of the housing
- solid strain reliefs for all Cable entries
- endstop, 7 mm mit transparent locking clip in scope of delivery
- solid ABS plastic housing
- lockable lid with 2 keys
- 1 x M20 - screw connection in scope of delivery
- delivery with installation material
- light grey (similar RAL 7035)

#### Features

General	
Labeling field	Yes
Classification	OS2 APC (8€)
Protection class IP	44
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	DE
GTIN (EAN)	4043921665756
Mounting types	
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	258
Width mm	207
Height mm	64
Net weight piece kg	0,824

Certifications	
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,953
Packaging unit Width mm	225
Packaging unit Height mm	285
Packaging unit Depth mm	118
References	
Accessories	228111430, 228111450, 228111470
Similar article	228100402, 228100404, 228100406