

LED recessed downlight  
Article no. 12108063

Light.  
For Generations.



Entwurf



#### Tender

LED recessed downlight, gold, Round. In a compact design, for installation in tool-less rapid assembly systems. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 500 mA, Power: 11W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 880lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 32°, Adjustability: Not adjustable, With control gear: No.

Article data	
Article no.	12108063
GTIN	4250047797579
Short description	LED recessed downlight
Material	Aluminium
Colour	Gold
Type of surface	Matt
Shape	Round
Outer diameter	82 mm
Built-in diameter	74 mm
Installation depth	74 mm
Weight	0.268 kg

LED recessed downlight  
Article no. 12108063

Light.  
For Generations.

Lighting technology	
Colour temperature	3000 K
Light colour	White
Light output	Direct
Luminous flux	880 lm
System efficiency	80 lm/W
Colour rendering	CRI > 90
Reflector	High-gloss
Beam angle	32°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	11 W
Voltage type	DC
DC nominal voltage max	12 V
Current	500 mA
Lamp	LED
Protection class	III
Degree of protection	IP20
Control	Dimming dependent on driver

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Plastic, transparent

Packing data	
Gross weight	0.316 kg
Length of packaging	100 mm
Packaging width	95 mm
Packaging height	115 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.