

Han 3A-C/P-f.Hood--DL-grey-w.cord



| Part number | 09 20 003 5442 | |
|---|--|--|
| Specification | Han 3A-C/P-f.HoodDL-grey-w.cord | |
| HARTING eCatalogue | https://b2b.harting.com/09200035442 | |
| Identification | | |
| Category | Hoods/Housings | |
| Series of hoods/housings Han A [®] | | |
| Type of hood/housing | Protection cover | |
| Description of hood/ housing | for hoods Thermoplastic With fixing cord | |

Version

| Locking type | Single locking lever |
|----------------------|---|
| Size | 3 A |
| Field of application | Standard Hoods/housings for industrial applications |
| Details | for mounted male insert |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|---|
| Degree of protection acc. to IEC 60529 | IP44 IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (locking) | Polyamide |
|---|------------------------|
| Colour (locking) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



| Material properties | |
|-----------------------------------|--------------|
| REACH SVHC substances | No |
| | |
| Specifications and approvals | |
| Approvals | DNV GL |
| | |
| | |
| Commercial data | |
| Commercial data Packaging size | 10 |
| | 10 9.54 g |
| Packaging size | |