

Han 3 EMC HOOD ANGLED ENTRY 2PEGS M20



| | |
|--------------------|---|
| Part number | 19 62 003 1640 |
| Specification | Han 3 EMC HOOD ANGLED ENTRY 2PEGS M20 |
| HARTING eCatalogue | https://b2b.harting.com/19620031640 |

Identification

| | |
|--------------------------|----------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] EMC |
| Type of hood/housing | Hoods |

Version

| | |
|----------------------|--|
| Locking type | Single locking lever |
| Size | 3 A |
| Version | Side entry |
| Cable entry | 1x M20 |
| Field of application | Hoods/Housings for higher EMC requirements |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP44 IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E | 12 |

Material properties

| | |
|-----------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |



Pushing Performance

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 10 |
| Net weight | 80.7 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |