LED recessed spot

Article no. 12169153



Light. For Generations.





Tender

recessed spot, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 1.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 70lm, Colour temperature: 3000 K, Light colour : White, Adjustability: Pivoted, With control gear: No.

| Article data | |
|--------------------|-------------------|
| Article no. | 12169153 |
| GTIN | 4250047798095 |
| Short description | LED recessed spot |
| Material | Aluminium |
| Colour | Nickel |
| Type of surface | Matt |
| Shape | Round |
| Outer diameter | 45 mm |
| Built-in diameter | 38 mm |
| Installation depth | 35 mm |
| Weight | 0.070 kg |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 24.07.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED recessed spot

Article no. 12169153

BRUMBERG

Light. For Generations.

| Lighting technology | |
|---------------------------------------|--|
| Colour temperature | 3.000 K |
| Light colour | White |
| Light output | Direct |
| Luminous flux | 70 lm |
| System efficiency | 58 lm/W |
| Colour rendering | CRI > 80 |
| Reflector | Without |
| Light sharing | Symmetric |
| 2.8.10 0.10111.6 | oj.m.iou.io |
| Operating technology of the luminaire | |
| System output | 1.2 W |
| Voltage type | DC |
| Current | 350 mA |
| Lamp | LED |
| Lamp holder | Plug&Play |
| Protection class | |
| Degree of protection | IP20 |
| Control | Depending on a |
| | |
| Mounting technology | |
| Mounting method | Rec _ d mounting |
| Place of installation | Cung-n. unted |
| Adjustability | ivot |
| Swivel angle | 125° |
| Further references | o cover with thermal insulation material |
| Material cover | Plastic, transparent |
| | |
| Packing data | |
| Gross weight | 0.078 kg |
| Length of packaging | 70 mm |
| Packaging width | 70 mm |
| Packaging hight | 50 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that |
| | harmful substances get into the environment. |

Accessories