

## plug low voltage - with cable gland, Multi-Grip




| Product description       |                              |
|---------------------------|------------------------------|
| BALS-Prd.-Nr              | 4441                         |
| EAN                       | 4024941044417                |
| Product category          | ELV plug                     |
| Current                   | 32A                          |
| Number of poles           | 3p                           |
| Arrangement of phases     | 3P                           |
| Position of earth contact | 4 h                          |
| Voltage                   | 20 up to 25 and 40 up to 50V |
| Frequency                 | 100 - 200Hz                  |

| Product description    |  |
|------------------------|--|
| Protection degree      | IP44   |
| Colour code            | green RAL 6002   |
| Colour of appliance    | Collar green RAL 6002, Housing cover grey RAL 7035, Cable gland grey RAL 7035  |
| Connection design      | with screw terminal  |
| Maximum conductor size | 10,0 qmm   |
| Cable entry            | with cable gland   |
| Height                 | 141mm  |
| Width                  | 62mm   |
| Depth                  | 57mm   |
| Material of enclosure  | Polyamide  |
| Contacts               | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Additional technical properties |  |
|---------------------------------|--|
|                                 | Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.158 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941044417    |

| Logistics data |               |
|----------------|---------------|
| Length         | 57 mm         |
| Width          | 62 mm         |
| Height         | 141 mm        |
| Weight         | 0.159 kg      |
| Volume         | 498.294 ccm   |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941968188 |
| Length         | 248 mm        |
| Width          | 158 mm        |
| Height         | 123 mm        |
| Weight         | 1.677 kg      |
| Volume         | 3,960 ccm     |



16 MB 43

| Ampere Polzahl             | 16<br>2 | 16<br>3 | 32<br>2 | 32<br>3 |
|----------------------------|---------|---------|---------|---------|
| a                          | 62,0    | 62,0    | 62,0    | 62,0    |
| b                          | 85,0    | 85,0    | 85,0    | 85,0    |
| c                          | 140,0   | 140,0   | 140,0   | 140,0   |
| d                          | 55,0    | 55,0    | 55,0    | 55,0    |
| e                          | 50,0    | 50,0    | 50,0    | 50,0    |
| f Ø                        | 24,5    | 24,5    | 24,5    | 24,5    |
| Leiter mm <sup>2</sup> min | 4       | 4       | 4       | 4       |
| Leiter mm <sup>2</sup> max | 10      | 10      | 10      | 10      |
|                            |         |         |         |         |
|                            |         |         |         |         |
|                            |         |         |         |         |

