

BIRO CIRCLE LED surface mounted ring light, direct, DALI dimmable

Article no. 13571178

Light.
For Generations.**Tender**

LED surface mounted ring light, direct, DALI dimmable, Round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Light colour : White, Beam angle: 110°, With control gear: Yes, Control: DALI.

Article data

Article no.	13571178
GTIN	4251433971566
Series name	BIRO CIRCLE
Short description	LED surface mounted ring light, direct, DALI dimmable
Material	Aluminium / Steel / Plastic
Shape	Round
Outer diameter	750 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage
Weight	6.000 kg

Lighting technology

Light colour	White
Light output	Direct
System efficiency	50 lm/W
Colour rendering	CRI > 80
Reflector	Without
Beam angle	110°
Light sharing	Symmetric

BIRO CIRCLE LED surface mounted ring light, direct, DALI dimmable

Article no. 13571178

Light.
For Generations.

Operating technology of the luminaire	
System output	50 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Control	DALI
Bulb change possible	Yes

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Material cover	Plastic, opal

Packing data	
Gross weight	7 kg
Length of packaging	780 mm
Packaging width	780 mm
Packaging height	110 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.