
BRUMBERG

MINI LED track spotlight

Article no. 88394683

Light. For Generations.







Tender

LED track spotlight, Round., Hight 200.0 mm Weight 0.839 kg, with rotattionssymmetrical, deep, wide distributed light intensity. Luminous flux 2.686 lm, Power 1 x 23 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 90, Housing material: Aluminium / Glass / Plastic, Colour: Silver, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, . With electronic driver, DALI dimmable.

| Article data | |
|-------------------|-----------------------------|
| Article no. | 88394683 |
| GTIN | 4251433980780 |
| Series name | MINI |
| Short description | LED track spotlight |
| Material | Aluminium / Glass / Plastic |
| Colour | Silver |
| Shape | Round |
| Length | 71 mm |
| Hight | 200 mm |
| Weight | 0.839 kg |

BRUMBERG

MINI LED track spotlight

Article no. 88394683

Light. For Generations.

| Lighting technology | |
|------------------------------|------------|
| Light colour | White |
| Luminous flux | 2,686 lm |
| System efficiency | 117 lm/W |
| Colour rendering | CRI > 90 |
| Reflector | High-gloss |
| Light sharing | Symmetric |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| System output | 24 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequenz max. | 50 Hz |
| Lamp | LED |
| Lamp holder | Without fitting |
| Protection class | |
| Degree of protection | IP20 |
| Control | DALI |
| Bulb change possible | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |

| Mounting technology | |
|-----------------------------|-------------------------------|
| Mounting method | Conductor rail mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Rotatable and adjustable head |
| Swivel angle | 180° |
| Rotation angle | 350° |
| Head adjustable angle | 90° |
| Suitable for through-wiring | No |

| Packing data | |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Gross weight | 0.968 kg |
| Length of packaging | 295 mm |
| Packaging width | 120 mm |
| Packaging hight | 170 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |