
## BRUMBERG


## TRAXX MICRO LED track spotlight, on/off switchable

Article no. 88694184

Light. For Generations.









## Tender

LED track spotlight, on/off switchable, Round.Luminaire diameter 40.0 mm, Weight 0.272 kg, with rotattionssymmetrical, deep, wide distributed light intensity.Luminous flux 1.340 lm, Power 1 x 11 W, Light colour neutral white, Correlated color temprature (CCT) 4.000 K, Colour rendering index CRI > 90, Rated life time L80/B10 at 25 °C: 50.000 h, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Glass / Plastic, Colour: Black structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20, .With electronic driver, on/off switchable.

| Article data      |  |
|-------------------|--|
| Article no.       | 88694184                               |
| GTIN              | 4251433978664                          |
| Series name       | TRAXX MICRO                            |
| Short description | LED track spotlight, on/off switchable |
| Material          | Aluminium / Glass / Plastic            |
| Colour            | Black                                  |
| Type of surface   | Structure                              |
| Shape             | Round                                  |
| Outer diameter    | 40 mm                                  |
| Weight            | 0.272 kg                               |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 16.09.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## TRAXX MICRO LED track spotlight, on/off switchable

Article no. 88694184

Light. For Generations.

**BRUMBERG** 

| Lighting technology          |            |
|------------------------------|------------|
| Colour temperature           | 4.000 K    |
| Light colour                 | White      |
| Luminous flux                | 1,340 lm   |
| System efficiency            | 122 lm/W   |
| Colour rendering             | CRI > 90   |
| Reflector                    | High-gloss |
| Beam angle                   | 40°        |
| Light sharing                | Symmetric  |
| Adjustable color temperature | No         |

| Operating technology of the luminaire |  |
|---------------------------------------|--|
| System output                         | 11 W   |
| Voltage type                          | AC   |
| AC nominal voltage max                | 230 V  |
| Frequenz max.                         | 50 Hz  |
| Lamp                                  | LED  |
| Protection class                      |  |
| Degree of protection                  | IP20   |
| Control                               | on/off   |
| Bulb change possible                  | The light source of this luminaire may only be replaced by the manufacturer or a service |
| buin change hossinie                  | technician commissioned by him or a similarly qualified person.                          |
| Rated life time L80/B50 at 25 °C      | 50.000 h   |

| Mounting technology         |                               |
|-----------------------------|-------------------------------|
| Mounting method             | Surface mounting              |
| Place of installation       | Ceiling-mounted               |
| Adjustability               | Rotatable and adjustable head |
| Swivel angle                | 90°                           |
| Rotation angle              | 350°                          |
| Head adjustable angle       | 90°                           |
| Suitable for through-wiring | No                            |

| Packing data            |  |
|-------------------------|--|
| Gross weight            | 0.329 kg   |
| Length of packaging     | 225 mm   |
| Packaging width         | 105 mm   |
| Packaging hight         | 105 mm   |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.<br>By disposing of electrical waste and other old or defective electronics separately, you |
|                         | support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.   |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 16.09.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/