

Han 24B-HMC-asg1-LB-M25



Part number	19 30 224 1251
Specification	Han 24B-HMC-asg1-LB-M25
HARTING eCatalogue	https://b2b.harting.com/19302241251

Identification

Category	Hoods/Housings
Series of hoods/housings Han® HMC	
Type of hood/housing	Surface mounted housing
Туре	Low construction

Version

Locking type	Single locking lever
Han-Easy Lock [®]	Yes
Size	24 B
Version	Side entry
Cable entry	1x M25
Field of application	Special hoods and housings for high mating cycles

Technical characteristics

Limiting temperature	-40 +125 °C
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate Stainless steel
Colour (locking)	RAL 7037 (dust grey)



Material properties

Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Approvals DNV GL

Commercial data

Packaging size	1
Net weight	319.9 g
Country of origin	Germany
European customs tariff number	85389099