

Han B Hood Top Entry HC 2 Reels PG 29



| Part number | 09 30 016 0441 |
|--------------------|--|
| Specification | Han B Hood Top Entry HC 2 Reels PG 29 |
| HARTING eCatalogue | https://b2b.harting.com/09300160441 |

Identification

| Category | Hoods/Housings |
|---------------------------------|-------------------|
| Series of hoods/housings Han® B | |
| Type of hood/housing | Hoods |
| Туре | High construction |

Version

| Locking type | Single locking lever |
|----------------------|---|
| Size | 16 B |
| Version | Top entry |
| Cable entry | 1x Pg 29 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|---|
| Degree of protection acc. to IEC 60529 | IP65 IP67 in combination with special bulkhead mounted housings |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-----------------------------|-----------------------------|
| Surface (hood/housing) | Powder-coated Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Material properties

|--|

Specifications and approvals

| Approvals | DNV GL |
|-----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 202.7 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |