


LED Flutlichtstrahler FLIXX[®] 10 W, 4000 K, 900 lm

4 046725 359098

Leistungsmerkmale

Mit der neuen RED Serie FLIXX[®] haben wir nun interessante Lösungen für entsprechende Anforderungen mit unseren LED Flutlichtstrahler. Die robusten und hochwertigen Strahler aus Aluminiumdruckguss können sowohl privat wie auch gewerblich optimal eingesetzt werden. FLIXX[®] bietet somit vielfältige Einsatzbereiche sowohl im Innen- wie auch im Außenbereich an.

Niedriger Energieverbrauch, geringe Wärmeentwicklung, hohe Stoßfestigkeit sowie eine gute Farbwiedergabe sind nur einige Vorteile von FLIXX[®]. Der schwarze Strahler besticht zudem durch seine sehr flache Bauform.

Weitere Daten: 30.000 Stunden Lebensdauer LED, 15.000 Schaltzyklen, 115° Abstrahlwinkel, 0,5m Zuleitung, Aludruckgussgehäuse, Glasdifusor, Gewicht 0,54 kg, 2 Jahre Funktionsgarantie, Maße 136x147x41 mm.

DEHA Nummer

5759833

Artikelnummer

5710-30-0001

EAN-Nummer

4046725359098

Kennzeichnung


30.000h

CRI
>80

IP
54

W
10

IK
05

K
4.000

lm
900

2
Jahre
Funktions-
garantie



115°



A
↑
G **F**

LED Flutlichtstrahler FLIXX[®] 10 W, 4000 K, 900 lm

Allgemeine Daten

Elektrische Daten

Betriebsspannung	220-240 V AC
Nennleistung	10 W
Netzfrequenz	50/60 Hz
Dimmbar	Nein

Lichttechnische Daten

Farbwiedergabeindex	CRI >80, SDCM <6
Powerfaktor	> 0,8
Lichtstrom	900 Lumen
Lichtfarbe	4000 K (neutralweißes Licht)

Zusätzliche Daten

Lichtquelle	Nicht auswechselbares LED-Modul
Schutzart	IP54
Schutzklasse/Schutzart	1/IK05
Abstrahlwinkel	115°
Anzahl der Schaltzyklen	15.000, Failure Rate <0,2%
Nennlebensdauer	30.000 h

Mechanische Daten

Material	Glasdiffusor, Aludruckgehäuse
Maße HxBxT	136x147x41 mm
Gewicht	0,54 kg


Sonstiges

0,5 m Zuleitung (3x1,0 mm²)

The energy label features the EU flag and the word 'ENERGY' with a lightning bolt icon. Below this, the brand 'RED' and model number '5759833' are listed. A vertical scale of energy efficiency classes from A (green) to G (red) is shown, with class 'F' highlighted in black. The energy consumption is specified as '10 kWh/1000h'. A QR code and the date '2019/2015' are located at the bottom right of the label.

Bestelldaten

DEHA-Nr.	Type	EAN	Farbe	VPE
5759833	LED Flutlichtstrahler FLIXX [®] 10 W	4046725359098	Schwarz	1 Stk.



4 046725 359098

Performance features

With the new RED series FLIXX[®] now we have interesting solutions for appropriate requirements with our LED floodlights. The robust and high-quality spotlight die cast aluminium can be used both private and commercially.

FLIXX[®] thus offers a wide range of applications both indoors and outdoors.

Low energy consumption, low heat generation, a high impact resistance as well as a good colour rendering just to mention a few benefits of our FLIXX[®] series.

The black spotlight also has a very flat design.

Additional data: 30,000 hours life LED, 15,000 switching cycles, 115° beam angle, 0.5 m supply line, die cast aluminium housing, weight 0.54 kg, 2 years functional warranty, dimensions 136x147x41 mm.

DEHA number

5759833

Item number

5710-30-0001

EAN number

4046725359098

labels


30.000h

CRI
>80

IP
54

W
10

IK
05

K
4.000

lm
900

2
Jahre
Funktions-
garantie

115°



LED floodlight FLIXX[®] 10 W, 4000 K, 900 lm

General Data

Electrical data	
Operating voltage	220-240 V AC
Rated capacity	10 W
Power frequency	50/60 Hz
dimnable	No

Lighting data	
Colour rendering index	CRI >80, SDCM <6
Power factor	> 0,8
Luminous flux	900 Lumen
Light colour	4000 K

Further data	
Light source	Non-replaceable LED module
Protection	IP54
Protection class / degree of protection	1/IK05
Beam angle	115°
Number of switching cycles	15.000, Failure Rate <0,2%
Rated life	30.000 h

Mechanical data	
Material	Glass, die cast aluminium housing
Dimensions HxBxT	136x147x41 mm
Weight	0,54 kg

Further data	
A 0.5 m supply line (3x1,0 mm ²)	

ENERGY

RED
5759833

A
B
C
D
E
F
G

F

10
kWh/1000h

2019/2015

Order Data

DEHA-Nr.	Type	EAN	colour	VPE
5759833	LED floodlight FLIXX [®] 10 W	4046725359098	Black	1 pc.