## **Recessed ceiling spot** Article no. 88472683

For Generations.

Light.

BRUMBERG



## Tender

recessed ceiling spot, silver, round. In a compact design, for installation in tool-less rapid assembly systems. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Steel / Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 4.100lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 20°, Adjustability: Rotable and pivoted, With control gear: Yes.

Article data	
Article no.	88472683
GTIN	4250047779681
Short description	Recessed ceiling spot
Material	Steel / Aluminium
Colour	Silver
Type of surface	Matt
Shape	Round
Outer diameter	221 mm
Built-in width	200 mm
Installation depth	200 mm
Weight	2.403 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 24.07.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## **Recessed ceiling spot**

Article no. 88472683

## Light.

**BRUMBERG** 

For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	4,100 lm
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	20°
Light sharing	Symmetric

Operating technology of the luminaire		
System output	41 W	
Voltage type	AC	
AC nominal voltage max	230 V	
Frequenz max.	50 Hz	
Lamp	LED	
Protection class	11	
Degree of protection	IP20	

Mounting technology	
Mounting method	Recess 1 nou.
Place of installation	Ceiling、 nted
Adjustability	Rot and prvoted
Swivel angle	2.
Rotation angle	.5°
Further references	No over with thermal insulation material
Suitable for through-wiring	

Packing data	
Gross weight	2.67 kg
Length of packaging	310 mm
Packaging width	310 mm
Packaging hight	200 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.