
BRUMBERG

CORE LED recessed spotlight


Article no. 88677183





Light.

For Generations.



	₩ 4,44 1lm	38°	~ 230V	LDT-Data
--	---------------	-----	-----------	----------

Tender

LED recessed spotlight CORE, Round. Ceiling cut-out Ø 190 mm, Installation depth 180 mm, Outer diameter 205 mm, Weight 1,696 kg, with rotattionssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a glass transparent cover. Luminous flux 4.441 lm, Power 1 x 48,9 W, System Efficiency 91 lm/W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium / Glass, Colour: Black, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, on/off switchable.

Article data	
Article no.	88677183
GTIN	4251433900207
Series name	CORE
Short description	LED recessed spotlight
Material	Aluminium / Glass
Colour	Black
Type of surface	Matt
Shape	Round
Outer diameter	205 mm
Built-in diameter	190 mm
Installation depth	180 mm
Weight	1.696 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 03.05.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

BRUMBERG

CORE LED recessed spotlight

Article no. 88677183

Light. For Generations.

Lighting technology	
Colour temperature	3.000 К
Light colour	White
Light output	Direct
Luminous flux	4,441 lm
System efficiency	91 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	38°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	48.9 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Rotable and pivoted
Swivel angle	45°
Rotation angle	350°
Further references	No cover with thermal insulation material
Material cover	Glass transparent

Packing data	
Gross weight	1.993 kg
Length of packaging	240 mm
Packaging width	195 mm
Packaging hight	240 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 03.05.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/