



Product Features

FTTH-connection set, with wall jack, for surface mounting, with 2xLC-D - couplings (SM/APC), with 30 m cable 4 x G657 A2

- cable with 4 fibres in a cardboard reel for easy installation
- single ended assembled Cable for easy installation at the wall jack in the apartment
- plug confection 4 x LC/APC 8°, with captive shutter
- drop cable 4 x E9/125 G657 A2, Ø 4 mm, CPR class Eca, for internal use
- clearly arranged fibre management in the wall jack
- 2 free ports for retrofitting in the wall jack
- protection class of wall jack: IP45
- temperature range: -40° C - 70° C
- installation material included
- pure white (similar RAL 9010)

Features

General	
Surface	high-gloss
Classification	OS2 APC (8€)
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	CN
GTIN (EAN)	4043921665695
Mounting types	
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	100
Width mm	80
Height mm	29
Net weight piece kg	0,55
Certifications	
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,73
Packaging unit Width mm	260
Packaging unit Height mm	90
Packaging unit Depth mm	266

FTTH-Anschlussset 2xLC-D OS2 APC 30m

Article no.: 228111430

Color: purewhite (ähnlich RAL-Nr. 9010)

References	
Accessories	228100402, 228100404, 228100406, 228100412
Similar article	228111450, 228111470