



Product Features

APL house connection box, surface mounting, lockable, with 6 x LC-D - couplings (SM/APC)

- well organized and tidy entry of Micro pipe systems
- hinges splice cassette (the bending radius is maintained when opened)
- clear fibre - and splice management in splice cassette
- splice cassette for holding 24 pigtails
- integrated comb for holding crimp splices
- ready to splice with exposed and inserted pigtails incl. 6 x LC-D- ceramic couplings green
- LC-fibre pigtails E9/125 µm, 2 m, SM OS2 APC, grade B1, G657.A
- with test protocol for all fibres incl. serial number
- 12 drop-cable entries (3mm Ø) at the bottom of the housing
- 2 cable entries (M20) at the bottom of the housing
- optional Cable entry at the top of the housing
- solid strain reliefs for all Cable entries
- endstop, 7 mm mit transparent locking clip in scope of delivery
- solid ABS plastic housing
- lockable lid with 2 keys
- 1 x M20 - screw connection in scope of delivery
- delivery with installation material
- light grey (similar RAL 7035)

Features

General

Labeling field	Yes
Protection class IP	44
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	DE
GTIN (EAN)	4043921665749

Mounting types

surface-mounted	Yes
-----------------	-----

Dimensions/Weights without packaging

Length mm	258
Width mm	207
Height mm	64
Net weight piece kg	0,783

Certifications

RoHS conform	Yes
--------------	-----

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,91
Packaging unit Width mm	225
Packaging unit Height mm	285
Packaging unit Depth mm	118
References	
Accessories	228111430, 228111450, 228111470
Similar article	228100402, 228100404, 228100412