


DURACELL®

CR2032

Lithium/Manganese Dioxide Battery

Li/MnO₂



SPECIFICATIONS

Nominal Voltage: 3.0 V

Typical Voltage: 3.1 – 3.3 V

Rated Capacity: 210 mAh on
15 k Ω to 2.0 V

Average Weight: 3.2 g (0.113 oz.)


Terminals: Flat

Operating Temp. Range: -20°C to 60°C
(-4°F to 140°F)


NEDA/ANSI: 5004LC

IEC: CR2032

Discharge Characteristics



Temperature Characteristics




DURACELL®

BATTERIES


Berkshire Corporate Park
Bethel, CT. 06801 U.S.A.
Telephone: Toll-free 1-800-544-5454
www.duracell.com

Delivered capacity is dependent on the applied load, operating temperature and cut-off voltage. Please refer to the charts and discharge data shown for examples of the energy/service life that the battery will provide for various load conditions.


Load vs. Operating Voltage




Load vs. Capacity



Pulse Discharge Characteristics



Storage Characteristics



DURACELL[®]

BATTERIES

Berkshire Corporate Park
Bethel, CT. 06801 U.S.A.
Telephone: Toll-free 1-800-544-5454
www.duracell.com

Delivered capacity is dependent on the applied load, operating temperature and cut-off voltage. Please refer to the charts and discharge data shown for examples of the energy/service life that the battery will provide for various load conditions.