

Leistungsmerkmale

Die MELTY[®] Heizlüfter Serie, erhältlich in 3 kW, 5 kW, 9 kW, 15 kW sowie 30 kW Leistung in Industriequalität, ist für den mobilen Einsatz in unterschiedlichen Bereichen konzipiert. Der leistungsstarke Ventilator mit hoher Wurfweite und die vertikal verstellbaren Luftleitlamellen sorgen für eine optimale Wärmeverteilung.

Die Heizelemente aus rostfreiem Stahl erlauben den Einsatz auch in staubigen Umgebungen und sorgen für eine lange Lebensdauer. Das robuste Metallgehäuse hat einen stabilen Tragegriff und die Platzierung der Bedienelemente befindet sich geschützt auf der Rückseite.

An die Modelle ab 5 kW kann ein Wärmeableitschlauch angebracht werden, so dass das Gerät außerhalb des zu heizenden Bereichs aufgestellt werden kann.

Optionales Zubehör: Wärmeableitschlauch
Ø 240 mm flexibel bis zu 6 m Länge (7136181)

Technische Daten

- Einstellbare Leistungsstufen:
80 (Ventilator)/2500/5000 W
- Inkl. 1,1 m Kabel mit CEE-Stecker 16 A
- Inkl. Tragegriff, für empfohlene Raumgröße von bis ca. 48 m²

DEHA-Nummer

7136177

Artikelnummer

6410-30-0002

EAN

4046725401520

Kennzeichnung

MELTY[®] industrielles Heizgerät 5 kW



Allgemeine Daten

Merkmale	
Heizleistung	5 kW
Luftmenge	700 cbm/h
Anschlussspannung	380 V
Leistungsaufnahme	5 kW
Überhitzungsschutz	ja
Anzahl der Leistungsstufen	3
Mit Belüftungsstufe	ja
Mit Raumthermostat	ja
Schutzart (IP)	IPX4
Vorrichtung für Luftransportschlauch	ja
Durchmesser Abluft	240 mm
Farbe	schwarz
Breite	375 mm
Höhe	240 mm
Tiefe	395 mm

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7136177	MELTY [®]	6410-30-0002	4046725401520	1 Stück



Performance features

The MELTY[®] fan heater series, available in 3 kW, 5 kW, 9 kW, 15 kW and 30 kW output in industrial quality, is designed for mobile use in different areas. The powerful fan with a long throw and the vertically adjustable air guide fins ensure optimal heat distribution.

The stainless steel heating elements allow use even in dusty environments and ensure a long service life. The robust metal housing has a sturdy carrying handle and the placement of the controls is protected on the back.

A heat dissipation hose can be attached to models from 5 kW so that the device can be placed outside the area to be heated.

Optional accessories: heat dissipation hose
Ø 240 mm flexible up to 6 m long (7136181)

Technical data

- Adjustable power levels
80 (ventilator)/2500/5000 W
- Incl. 1.1 m cable with CEE plug 16 A
- Incl. carrying handle, for heating surfaces of up to approx. 48 m²

DEHA number

7136177

Item number

6410-30-0002

EAN

4046725401520

label

General Data

Features	
Heating capacity	5 kW
Air volume	700 cbm/h
Connection voltage	380 V
Power consumption	5 kW
Overheating protection	yes
Number of power levels	3
Ventilation position	yes
With room temperature controller	yes
Degree of protection (IP)	IPX4
Facility for air transport hose	yes
Diameter exhaust	240 mm
Colour	Black
Width	375 mm
Height	245 mm
Depth	395 mm

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
7136177	MELTTY [®]	6410-30-0002	4046725401520	1 Piece