



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 02 00	ProtExB 02	260 x 260 x 205
35.06 02 00	ProtExe 02	260 x 260 x 205
36.06 02 00	ProtExi 02	260 x 260 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	98	75
16	43	34
20	34	25
25	18	13
32	10	7
40	6	4
50	4	4
63	4	2
75		
85		

Tragschiene	TS 35
Länge (mm)	198
max. Bestückungslänge (mm)	153
Außenerde Bolzen	M10

	1,5	2,5	4	6	10	16	25	35	50	70	95
	99	81	66	51	26	22	9	9	7	5	
	3	3	3	3	2	2	1	1	1	1	
 A	6										
	10	60	108								
	16	23	41	67							
	20	9	25	43	72						
	25		12	26	43						
	35			8	20	39					
	50				3	16	32	104			
	63					5	18	35			
	80						7	19	32		
	100							9	17	32	
	125								7	16	31
	160									6	14
	200										6
	225										2
	250										
	315										
400											
500											



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 03 00	ProtExB 03	306 x 306 x 205
35.06 03 00	ProtExe 03	306 x 306 x 205
36.06 03 00	ProtExi 03	306 x 306 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	125	98
16	58	43
20	43	34
25	24	18
32	13	10
40	8	6
50	6	4
63	6	4
75		
85		

Tragschiene	TS 35
Länge (mm)	244
max. Bestückungslänge (mm)	199
Außenerde Bolzen	M10

	1,5	2,5	4	6	10	16	25	35	50	70	95	
	176	144	90	66	54	30	24	12	9	7	7	
	4	4	3	3	3	2	2	1	1	1	1	
 A	6											
	10	64	116									
	16	24	43	72								
	20	10	27	46	77							
	25		13	28	46							
	35			9	21	41						
	50				3	17	34	111				
	63					6	19	37				
	80						8	20	34			
	100							9	18	34		
	125								8	18	33	
	160									7	15	27
	200										6	13
	225										2	8
	250											4
	315											
400												
500												

	Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
	34.06 04 00	ProtExB 04	380 x 260 x 205
	35.06 04 00	ProtExe 04	380 x 260 x 205
	36.06 04 00	ProtExi 04	380 x 260 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262

	1,5	2,5	4	6	10	16	25	35	50	70	95	120	
	186	150	126	93	52	42	18	18	13	10	5	4	
U N	5	5	4	4	4	3	2	2	1	1	1	1	
	6												
	10	63	114										
	16	24	43	71									
	20	10	26	45	76								
	25		13	28	45								
	35			8	21	41							
	50				3	17	34	109					
	63					6	19	37					
	80						7	20	33				
	100							9	18	33			
	125								8	17	32		
	160									7	15	27	68
	200										6	13	21
	225										2	8	14
	250											4	10
	315												2
400													
500													

M	Seite	
	A/B	C/D
12	98	125
16	43	58
20	34	43
25	18	24
32	10	13
40	6	8
50	4	6
63	4	6
75		
85		

Tragschiene	TS 35
Länge (mm)	198
max. Bestückungslänge (mm)	153
Außenerde Bolzen	M10

	Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
	34.06 05 00	ProtExB 05	458 x 382 x 205
	35.06 05 00	ProtExe 05	458 x 382 x 205
	36.06 05 00	ProtExi 05	458 x 382 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262

	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240
	400	325	252	192	132	84	51	44	26	13	13	10	8	7	7
U N	5	5	4	4	4	3	2	2	2	1	1	1	1	1	1
	6														
	10	73	133												
	16	28	50	83											
	20	12	31	52	88										
	25		15	32	53										
	35			10	24	48									
	50				3	19	39	127							
	63					7	22	43							
	80						9	23	39						
	100							11	21	39					
	125								9	20	38				
	160									8	18	31	79		
	200										7	15	25	43	
	225										2	9	17	26	53
	250											5	11	18	29
	315												2	7	13
400														3	9
500															

M	Seite	
	A/B	C/D
12	147	179
16	67	79
20	53	63
25	28	34
32	16	19
40	8	9
50	8	8
63	6	8
75		
85		


Tragschiene	TS 35
Länge (mm)	320
max. Bestückungslänge (mm)	275
Außenerde Bolzen	M10





Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 06 00	ProtExB 06	480 x 480 x 205
35.06 06 00	ProtExe 06	480 x 480 x 205
36.06 06 00	ProtExi 06	480 x 480 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240		
	602	483	348	264	175	116	69	69	36	28	14	11	11	10	10		
LN	5	5	5	4	4	4	3	3	2	2	2	1	1	1	1		
	6																
	10	79	144														
	16	30	54	90													
	20	13	33	57	96												
	25		16	35	57												
	35			11	27	51											
	50				4	21	43	138									
	63					7	24	46									
	80						10	25	42								
	100							11	23	42							
	125								10	22	41						
	160									8	19	34	86				
	200										8	16	27	47			
	225											3	10	18	28	57	
	250												5	12	20	32	
	315													3	7	14	25
400															3	10	
500																	


M	Seite	
	A/B	C/D
12	201	179
16	91	79
20	70	63
25	38	34
32	22	19
40	12	9
50	10	8
63	8	8
75		
85		

Tragschiene	TS 35
Länge (mm)	418
max. Bestückungslänge (mm)	373
Außenerde Bolzen	M10



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 07 00	ProtExB 07	500 x 350 x 205
35.06 07 00	ProtExe 07	500 x 350 x 205
36.06 07 00	ProtExi 07	500 x 350 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	
	450	365	244	184	111	93	50	50	22	18	15	7	7	6	6	
LN	5	5	5	4	3	3	3	3	2	2	1	1	1	1	1	
	6															
	10	72	131													
	16	28	49	81												
	20	11	30	51	87											
	25		15	32	52											
	35			10	24	47										
	50				3	19	39	125								
	63					7	21	42								
	80						9	23	38							
	100							10	21	38						
	125								9	20	37					
	160									8	17	30	78			
	200										7	15	24	42		
	225											2	9	16	26	52
	250												5	11	18	29
	315													2	7	12
400															3	9
500																

M	Seite	
	A/B	C/D
12	147	201
16	67	91
20	53	70
25	28	38
32	16	22
40	8	12
50	8	10
63	6	8
75		
85		


Tragschiene	TS 35
Länge (mm)	288
max. Bestückungslänge (mm)	243
Außenerde Bolzen	M10





Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 08 00	ProtExB 08	620 x 450 x 205
35.06 08 00	ProtExe 08	620 x 450 x 205
36.06 08 00	ProtExi 08	620 x 450 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240
	714	576	424	320	196	164	99	84	50	26	26	16	16	13	13
	9	9	8	8	6	5	4	4	3	2	2	1	1	1	1
	6														
	10	82	149												
	16	31	56	93											
	20	13	34	59	99										
	25		17	36	59										
	35			11	27	53									
	50				4	22	44	142							
	63					7	25	48							
	80						10	26	44						
	100							12	23	43					
	125								10	23	42				
	160									9	20	35	88		
	200										8	17	27	48	
	225											3	10	19	29
	250												6	13	20
	315													3	8
	400														3
	500														


M	Seite	
	A/B	C/D
12	201	255
16	91	115
20	70	88
25	38	48
32	22	28
40	12	16
50	10	14
63	8	12
75		
85		

Tragschiene	TS 35
Länge (mm)	438
max. Bestückungslänge (mm)	393
Außenerde Bolzen	M10



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 09 00	ProtExB 09	740 x 550 x 205
35.06 09 00	ProtExe 09	740 x 550 x 205
36.06 09 00	ProtExi 09	740 x 550 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240
	1184	952	700	525	300	250	160	120	63	51	34	26	20	17	17
	11	11	9	9	7	7	5	4	3	3	2	2	1	1	1
	6														
	10	92	167												
	16	35	63	104											
	20	15	39	66	111										
	25		19	41	66										
	35			12	31	60									
	50				4	24	49	159							
	63					8	27	54							
	80						11	29	49						
	100							13	26	49					
	125								12	25	47				
	160									10	22	39	99		
	200										9	19	31	54	
	225											3	12	21	33
	250												6	14	23
	315													3	9
	400														4
	500														

M	Seite	
	A/B	C/D
12	255	323
16	115	148
20	88	113
25	48	62
32	28	37
40	16	20
50	14	18
63	12	14
75		
85		

Tragschiene	TS 35
Länge (mm)	488
max. Bestückungslänge (mm)	443
Außenerde Bolzen	M10





Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 10 00	ProtExB 10	762 x 508 x 205
35.06 10 00	ProtExe 10	762 x 508 x 205
36.06 10 00	ProtExi 10	762 x 508 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	201	323
16	91	148
20	70	113
25	38	62
32	22	37
40	12	20
50	10	18
63	8	14
75		
85		

Tragschiene	TS 35
Länge (mm)	446
max. Bestückungslänge (mm)	401
Außenerde Bolzen	M10



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 11 00	ProtExB 11	860 x 640 x 205
35.06 11 00	ProtExe 11	860 x 640 x 205
36.06 11 00	ProtExi 11	860 x 640 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	250	358
16	116	158
20	86	126
25	48	68
32	26	38
40	16	18
50	12	16
63	12	16
75		
85		

Tragschiene	TS 35
Länge (mm)	578
max. Bestückungslänge (mm)	533
Außenerde Bolzen	M10



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 12 00	ProtExB 12	914 x 610 x 205
35.06 12 00	ProtExe 12	914 x 610 x 205
36.06 12 00	ProtExi 12	914 x 610 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	250	358
16	116	158
20	86	126
25	48	68
32	26	38
40	16	18
50	12	16
63	12	16
75		
85		

	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240			
	1701	1377	1024	776	468	325	208	208	117	62	62	30	30	26	26			
	14	14	12	12	9	8	6	6	4	3	3	2	2	2	2			
	6																	
	10	100	181															
	16	38	68	113														
	20	16	42	71	120													
	25		20	44	72													
	35			14	33	65												
	50				5	27	54	173										
	63					9	30	58										
	80						12	31	53									
	100							15	29	53								
	125								13	28	51							
	160									11	24	42	108					
	200										10	20	34	59				
	225											4	13	23	36	72		
	250												7	16	25	40		
	315													3	10	17	31	
	400															4	12	
	500																	2

Tragschiene	TS 35
Länge (mm)	548
max. Bestückungslänge (mm)	503
Außenerde Bolzen	M10



Bestell-Nr.	Typ	Abmessungen H x B x T (mm)
34.06 13 00	ProtExB 13	980 x 740 x 205
35.06 13 00	ProtExe 13	980 x 740 x 205
36.06 13 00	ProtExi 13	980 x 740 x 205

Max. Bestückungsmöglichkeiten für Kabelverschraubungen nach DIN 50262



M	Seite	
	A/B	C/D
12	294	402
16	134	182
20	106	140
25	56	76
32	32	44
40	16	24
50	16	20
63	12	16
75		
85		

	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240			
	2255	1815	1300	975	600	490	280	240	155	102	72	54	40	34	34			
	15	15	13	13	10	9	7	6	5	4	3	2	2	2	2			
	6																	
	10	111	201															
	16	43	76	125														
	20	18	47	79	133													
	25		23	49	80													
	35			15	37	72												
	50				5	30	60	192										
	63					10	33	65										
	80						13	35	59									
	100							16	32	59								
	125								14	31	57							
	160									12	27	47	119					
	200										11	23	37	65				
	225											4	14	25	40	80		
	250												8	17	28	45		
	315													4	11	19	35	
	400															5	14	
	500																	2

Tragschiene	TS 35
Länge (mm)	678
max. Bestückungslänge (mm)	633
Außenerde Bolzen	M10

