



### Product Features

IP switching actuator/sensor, 8 x 16 A, 1 A/D-inputs, with network connection and integrated WIFI-Accesspoint, for DIN-rail mounting, light grey (similar RAL 7035)

- for DIN-rail mounting (144 mm)
- protection class according to EN60529 - IP20
- integrated power supply: 100 V-240V AC/50-60 Hz
- power consumption: 10 VA max.
- local handling for the switching outputs
- temperature range -5°C to +45°C
- 8 switching outputs 16A/230V (cos phi 1, detachable, screwless plug-in terminal up to 2,5mm)
- 16 digital inputs for dry ccontacts
- switching outputs configurable for roller blinds (max.4)
- LED status indication of the switching outputs
- local handling for the switching outputs
- 2 A/D inputs for sensors 0-10 V / 4-20 mA, configurable
- 16 digital inputs for dry ccontacts (detachable screw terminals)
- extensive logic functions for connections of the Input parameters
- AND/OR links of the inputs
- time switching functions (annual time switch), with random generator
- alarming functions by mail
- and much more..
- cross-platform handling via web browser
- SmartPhone control via App for free (iOS/Android)
- UDP protocol assistance for all functions/parameters
- manual IP address specification or dynamic specification via DHCP
- operator guidance at languages D/GB/NL/F
- light grey (similar RAL 7035)
- pre defined scenarios e.g. "all out/on", presents simulation and much more
- 3 user defined scenarios configurable
- easy configuration via web browser
- network integration via LAN or WLAN
- network RJ45-port
- Link and activity LED für networkports
- integrated WLAN-Accesspoint (IEEE 802.3 b/g/n, 150 Mbit/s)
- with WLAN antenna and 2 m conduct
- service LED for WLAN
- USB front port (USB2.0) for adaption of A LTE/GSM-Stick
- reset knob at the front panel
- password protection

- connection to amazon Alexa or Google home via additional hardware (APPModule)
- cross-platform handling via web browser
- SmartPhone control via App for free (iOS/Android)
- UDP protocoll assistance for all functions/parameters
- API interface for all functions/parameters
- function expansion with <R> -Control Plus Extension 4 via interface on the side
- manual IP adrees specification or dynamic specification via DHCP
- operator guidance at languages D/GB/NL/F

### Features

General	
Protection class IP	21
Halogen Free	Yes
Statistical goods number	85415900
Country of manufacture	DE
GTIN (EAN)	4043921663936
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	144
Width mm	90
Height mm	59
Net weight piece kg	0,448
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,626
Packaging unit Width mm	185
Packaging unit Height mm	145
Packaging unit Depth mm	95
References	
Accessories	700802612, 700802613, 700802614, 700802616
Similar article	700802610, 700802615

