



Product Features

UAE-jack, single, surface mounting, 8 way, 8 screw terminals, pure white (similar RAL 9010)

- openings for 6- and 8-way plugs (RJ12 and RJ45)
- suitable for RJ11/12 without additional reducing adapters
- jacks positioned downward sloped
- screw terminals for wires up to 1mm Ø, 2 wires at each contact
- alternative LSA-terminals for one wire 0,4-0,63 mm Ø, AW 26-22, max. number of connections > 50-times
- gold plated contacts
- voltage: 125 V
- operation current: 1 A bei 50° C
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- contact withstand: < 20 mOhm
- according to the following standards:
- TIA/EIA-568-B.2-2001, Cat. 3
- life (insertions and withdrawals): > 2500 cycles
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

| General | |
|--------------------------------------|---------------|
| Surface | high-gloss |
| Design | jack |
| Classification | Cat.3 |
| Protection class IP | 20 |
| Halogen Free | Yes |
| Statistical goods number | 85369010 |
| Country of manufacture | DE |
| GTIN (EAN) | 4043921039489 |
| Mounting types | |
| DIN-Rail | Yes |
| surface-mounted | Yes |
| Dimensions/Weights without packaging | |
| Length mm | 65 |
| Width mm | 80 |
| Height mm | 26 |
| Net weight piece kg | 0,03 |

| Certifications | |
|--------------------------|------------------|
| WEEE | Yes |
| CE | Yes |
| RoHS conform | Yes |
| Logistics Information | |
| Packaging | box |
| Packaging unit Quantity | 10 |
| Packaging unit Weight kg | 0,38 |
| Packaging unit Width mm | 134 |
| Packaging unit Height mm | 134 |
| Packaging unit Depth mm | 82 |
| References | |
| Accessories | 10010070, 681072 |
| Similar article | 13010407 |



8 Kontakte

