



Product Features

UAE-jack, double, flush mounting, 2x8 way, 8 screw terminals, with spreading claws, suitable for the design wall plates of all well-known manufacturer

- openings for 6- and 8-way plugs (RJ12 and RJ45)
- suitable for RJ11/12 without additional reducing adapters
- metal mounting ring
- with spreading claws
- jacks positioned downward sloped
- screw terminals for wires up to 1mm Ø, 2 wires at each contact
- alternative LSA-terminals for one wire 0,4-0,63 mm Ø, AW 26-22, max. number of connections > 50-times
- gold plated contacts
- voltage: 125 V
- operation current: 1 A bei 50° C
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- contact withstand: < 20 mOhm
- according to the following standards:
- TIA/EIA-568-B.2-2001, Cat. 3
- life (insertions and withdrawals): > 2500 cycles
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

| General | |
|--|---------------|
| Support ring | Yes |
| Design | jack |
| Design capability | Yes |
| Classification | Cat.3 |
| Protection class IP | 20 |
| Halogen Free | Yes |
| Statistical goods number | 85369010 |
| Country of manufacture | DE |
| GTIN (EAN) | 4043921040775 |
| Mounting types | |
| floor outlet box/underfloor installation | Yes |
| flush-mounted | Yes |
| trunking installation | Yes |

| Dimensions/Weights without packaging | |
|--------------------------------------|--|
| Length mm | 70 |
| Width mm | 70 |
| Height mm | 29 |
| Net weight piece kg | 0,037 |
| Certifications | |
| WEEE | Yes |
| CE | Yes |
| RoHS conform | Yes |
| Logistics Information | |
| Packaging | box |
| Packaging unit Quantity | 10 |
| Packaging unit Weight kg | 0,45 |
| Packaging unit Width mm | 138 |
| Packaging unit Height mm | 146 |
| Packaging unit Depth mm | 73 |
| References | |
| Accessories | 10010001, 10010051, 10010055, 13510003, 13510053, 13510503, 13511503, 681072 |
| Similar article | 13010130, 13010246, 13010422 |

