

Datenblatt Art. 902.431

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK 2 Steckdosenleiste / DESK 2 power strip

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	13A / 250V~ 50Hz	Rated current / rated voltage Frequency	13A / 250V~ 50Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm²	Supply cable	0,2m H05VV-F 3G1,5mm²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Wieland GST18i3	Plug	Wieland GST18i3
Stromausgang		Power output	
Steckdosen 2x UK BS 1363 (Type G) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 45° Integrierte Sicherung 3,15 A 13A / 250V~, IP20		Socket outlets 2x UK BS 1363 (Type G) 2-pole with earthing contact With shutter Black, similar to RAL 9005, 45° Integrated Fuse 3,15A 13A / 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module 1x Custom Module leer		Custom Modules 1x Custom Modules empty	
USB-A Charger 15W (42,5mm) Doppelcharger	DC5V 3,1A	USB-A Charger 15W (42,5mm) Double charger	DC5V 3,1A
USB-Spezifikation	USB 3.0	USB standard	USB 3.0
Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material Gehäuse: Aluminium, nasslackiert, Inox		Material Housing: Aluminium, wet painted, Inox	
Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang 1x DESK 2 Steckdosenleiste inkl. Haltewinkel		Scope of delivery 1x DESK 2 power strip incl. mounting brackets	

Im Karton

In carton

Umgebungsbedingungen

Environmental conditions

Maximale Höhe 0 - 2000m
Umgebungstemperatur bei Montage und Nutzung 5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.
Umgebungstemperatur bei Transport und Lagerung -25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend) 5 – 95%
Schutzart IP20

Maximum height 0 - 2000m
Surrounding temperature during mounting and use 5°C – 35°C
Protect from direct sunlight.
Surrounding temperature during transport and storage -25°C - 60°C
Relative humidity (non-condensing) 5 – 95%
Protection type IP20

Konformität

Conformity

Angewandte Normen IEC 62368-1 (USB-Charger)
 EN 62368-1 (USB-Charger)

Applied standards IEC 62368-1 (USB-Charger)
 EN 62368-1 (USB-Charger)

