


B1



Push Mounts

- Require no adhesive or additional mounting hardware
- Can be used where only one side of the panel is accessible

B2



B3

C1

Part Number	Used with Cable Ties‡	Max. Panel Thickness		Panel Hole Diameter		Material	Color	Environment	Mounting Method	Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm						
PM2H25-C	M, I, S	0.125	3.2	0.250	6.4	Nylon 6.6	Natural	Indoors	Push Barb	100	500
PM2H25-M0	M, I, S	0.125	3.2	0.250	6.4	Weather Resistant Nylon 6.6	Black	Outdoors	Push Barb	1000	5000
PM2H25-M30	M, I, S	0.125	3.2	0.250	6.4	Heat Stabilized Nylon 6.6	Black	Indoors	Push Barb		

‡Cable tie cross section sizes: M = Miniature, I = Intermediate, and S = Standard.

C4


D1



Push Button Mounts

- Require no adhesive or additional mounting hardware
- Designed for use where both sides of the panel are accessible

D2



D3

E1

Part Number	Used with Cable Ties‡	Max. Panel Thickness		Panel Hole Diameter		Material	Color	Environment	Mounting Method	Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm						
PBMS-H25-C	M, I, S	0.13	3.2	0.250	6.4	Nylon 6.6	Natural	Indoors	Push Barb	100	1000
PBMS-H25-C14		0.13	3.2	0.250	6.4	Nylon 6.6	Gray				
PBMS-H25-M0	M, I, S	0.13	3.2	0.250	6.4	Weather Resistant Nylon 6.6	Black	Outdoors	Push Barb	1000	5000
PBMS-H25-M30	M, I, S	0.13	3.2	0.250	6.4	Heat Stabilized Nylon 6.6	Black	Indoors	Push Barb	1000	5000
PBMSL-H25-M30*		0.29	7.2	0.250	6.4						

‡Cable tie cross section sizes: M = Miniature, I = Intermediate, and S = Standard.

*not cULus listed

F

G

H