



Specification Sheet

CR2 & CR4H Closed Connector Rings

	<p>The Panduit CR2 and CR4H closed cable tie connector rings connect multiple wire bundles or hang bundles from conduit, eliminating the need for saddle clamps. These mounts can be used with various cable ties, and select versions can accommodate different environments. For color, material type, cable tie compatibility and dimensional information, see the table below. These come available in packs of 1000.</p>
--	---

Part Number	Material	Color	Used with Cable Ties *	Height In. (mm)	Length In. (mm)	Width In. (mm)
CR2-M	Nylon 6.6	Natural	M, I, S	.24 (6.1)	.20 (5.0)	.33 (8.4)
CR4H-M	Nylon 6.6	Natural	M, I, S, HS, LH	.36 (9.1)	.30 (7.6)	.57 (14.6)
CR4H-M0	Weather Resistant Nylon 6.6	Black	M, I, S, HS, LH	.36 (9.1)	.30 (7.6)	.57 (14.6)
CR4H-M30	Heat Stabilized Nylon 6.6	Black	M, I, S, HS, LH	.36 (9.1)	.30 (7.6)	.57 (14.6)

* Cable Tie cross section sizes: M = Miniature, I = Intermediate, S = Standard, HS = Heavy Standard, LH = Light Heavy

Environment: Indoor (CR2-M and CR4H-M, CR4H-M30); Outdoor (CR4H-M0)

Standards: cULus Type 2, 21 (File E136577)

Operating Temp: Natural / Weather Resistant: -76° F (-60° C) to 185° F (85° C)
Heat Stabilized: -76° F (-60° C) to 239° F (115° C)

Flammability: UL94 V-2

Package Qty: 1000