



Abbildung ähnlich

#### Product Features

Cat.6A iso universal plug, RJ45, shielded, for field assembly, color code T568A according to TIA/EIA-568-B.2

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- zinc diecast housing, Ni plated
- protection class: IP 20 according to IEC60529
- multi-port capable
- quick assembly without special tools
- color code T568A according to TIA/EIA-568-B.2
- cable diameter 5-9 mm
- IDC terminals for solid wires, outer diameter 0,51-0,64mm, AWG 24/1-AWG 22/1
- IDC terminals for stranded wires, outer diameter 0,46-0,76mm, AWG 27/7-AWG 22/7
- reconnectable > 4-times
- suitable for PoE++ / 4PPoE according to IEEE 802.3bt
- according to the following standards:
  - ISO/IEC 11801, Cat.6A, shielded
  - DIN EN 50173-1, Cat.6A, shielded
  - ANSI TIA/EIA-568-C.2, Category 6A
  - DIN EN 60603-7-51, 500 MHz, shielded
  - IEEE 802.3an, 10 Gbit-Ethernet
- temperature range: -40°C to 85°C
- life > 750 cycles

#### Features

General	
Surface	zinc die-cast, refined
Design	plug
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85366990
Country of manufacture	TW
GTIN (EAN)	4043921665855
Mounting types	
field finishing	Yes

Dimensions/Weights without packaging	
Length mm	49
Width mm	14
Height mm	17
Net weight piece kg	0,022
Certifications	
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,34
Packaging unit Width mm	300
Packaging unit Height mm	137
Packaging unit Depth mm	42
References	
Accessories	21207000, 39200012
Similar article	13900304, 13900320, 13900330

