

## R 15-7+E-ISK-BU



Part number	09 15 007 3121
Specification	R 15-7+E-ISK-BU
HARTING eCatalogue	<a href="https://b2b.harting.com/09150073121">https://b2b.harting.com/09150073121</a>

### Identification

Category	Inserts
Series	R15

### Version

Termination method	Crimp termination
Gender	Female
Number of contacts	7
Details	for metal hoods / housings

### Technical characteristics

Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Rated voltage acc. to CSA	600 V
Insulation resistance	$\geq 10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$

### Material properties

Material (insert)	Polyamide
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	HB
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No



Pushing Performance

## Material properties

REACH ANNEX XIV substances No

REACH SVHC substances No

## Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076  
CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size 10

Net weight 8.85 g

Country of origin Germany

European customs tariff number 85389099