

Han 16EMC/B-HTE-M25 (HT)



| Part number | 19 62 816 1421 |
|--------------------|-------------------------------------|
| Specification | Han 16EMC/B-HTE-M25 (HT) |
| HARTING eCatalogue | https://b2b.harting.com/19628161421 |

Identification

| Category | Hoods/Housings |
|--------------------------|----------------------------|
| Series of hoods/housings | Han [®] EMC/B |
| | Han [®] High Temp |
| Type of hood/housing | Hoods |
| Туре | Low construction |

Version

| Locking type | Double locking lever |
|--------------|----------------------|
| Size | 16 B |
| Version | Top entry |
| Cable entry | 1x M25 |

Technical characteristics

| Limiting temperature | -40 +125 °C -40 +200 °C With Han® High Temp components |
|--|---|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-----------------------------|--------------------|
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |



Specifications and approvals

| Approvals | DNV GL |
|-----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 150.2 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |