




AILIS LED panel 620 x 620 mm opal DALI-2

Article no. 32048073

Light.
For Generations.**Tender**

LED-Panel 620 x 620 mm Opal DALI-2, Square. Recessed luminaire for ceilings with visible mounting rails. Ceiling cut-out L x W 620 x 620 mm, Installation depth 12 mm, Length 620 mm, Width 620 mm, Weight 3,040 kg, with rotationssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a plastic, opal cover. Luminous flux 3.359 lm, Power 1 x 39 W, System Efficiency 86 lm/W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L80/B10 at 25 °C: 25.000 h, Rated life time L80/B20 at 25 °C: 28.000 h, Rated life time L80/B50 at 25 °C: >30.000 h, Housing material: Aluminium / Polycarbonate, Colour: White, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP40. With electronic driver, DALI-2 dimmable.

Product Benefits

- Square insertion luminaire for ceiling systems in grid size 625 x 625 mm.
- Opal design.
- Incl. dimmable DALI converter.
- Matched accessories available.

AILIS LED panel 620 x 620 mm opal DALI-2

Article no. 32048073

Light.
For Generations.

Article data	
Article no.	32048073
GTIN	4251433936763
Series name	AILIS
Short description	LED panel 620 x 620 mm opal DALI-2
Material	Aluminium / Polycarbonate
Colour	White
Shape	Square
Built-in width	620 mm
Built-in length	620 mm
Installation depth	12 mm
Length	620 mm
Width	620 mm
Hight	12 mm
Scope of delivery	incl. DALI-2 dimmable driver
Weight	3.040 kg

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	3,359 lm
System efficiency	86 lm/W
McAdam-Step	McAdam-Step 6
Colour rendering	CRI > 80
Reflector	Without
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	39 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	II
Degree of protection	IP40
Dimmable	Yes
Control	DALI-2
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L80/B10 at 25 °C	25.000 h
Rated life time L80/B20 at 25 °C	28.000 h
Rated life time L80/B50 at 25 °C	>30.000 h

Operating technology of the luminaire	
---------------------------------------	--

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
stamp	UKCA
Further references	No cover with thermal insulation material
Material cover	Plastic, opal

AILIS LED panel 620 x 620 mm opal DALI-2
Article no. 32048073Light.
For Generations.

Packing data	
Gross weight	3.83 kg
Length of packaging	650 mm
Packaging width	706 mm
Packaging height	45 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Accessories