

## plug - with TE screw terminals, for harsh applications




| Product description       |                     |
|---------------------------|---------------------|
| BALS-Prd.-Nr              | 2188                |
| EAN                       | 4024941021883       |
| Product category          | TE plug             |
| Current                   | 63A                 |
| Number of poles           | 5p                  |
| Arrangement of phases     | 3p+N+PE             |
| Position of earth contact | 9 h                 |
| Voltage                   | 120/208 - 144/250V~ |
| Frequency                 | 50/60Hz             |

| Product description    |  |
|------------------------|--|
| Protection degree      | IP67   |
| Colour code            | blue RAL 5015  |
| Colour of appliance    | Collar blue RAL 5015, Pusher black RAL 9005, Housing cover dark grey RAL 7012, Cable gland dark grey RAL 7012, Bajonet ring dark grey RAL 7012 |
| Connection design      | screw terminal as box terminal   |
| Maximum conductor size | 16,0 qmm   |
| Cable entry            | with cable gland   |
| Height                 | 234mm  |
| Width                  | 114mm  |
| Depth                  | 114mm  |
| Material of enclosure  | Polyamide  |
| Contacts               | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                                       |

| Additional technical properties |  |
|---------------------------------|--|
|                                 | For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket and integrated strain relief |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.705 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941021883    |

| Logistics data |               |
|----------------|---------------|
| Length         | 114 mm        |
| Width          | 114 mm        |
| Height         | 234 mm        |
| Weight         | 0.706 kg      |
| Volume         | 3,041.064 ccm |
| Packaging      | Carton        |
| Content amount | 5 ST          |
| EAN            | 4024941952712 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 3.731 kg      |
| Volume         | 13,588.4 ccm  |



|                           | 63<br>Polzahl<br>3 | 63<br>4 | 63<br>5 |
|---------------------------|--------------------|---------|---------|
| ø a                       | 114,0              | 114,0   | 114,0   |
| b                         | 153,0              | 153,0   | 153,0   |
| d                         | 171,0              | 171,0   | 171,0   |
| ø e                       | 36,0               | 36,0    | 36,0    |
| x                         | 233,0              | 233,0   | 233,0   |
| y                         | 114,0              | 114,0   | 114,0   |
| z                         | 114,0              | 114,0   | 114,0   |
| Cond. mm <sup>2</sup> min | 6,0                | 6,0     | 6,0     |
| Cond. mm <sup>2</sup> max | 16,0               | 16,0    | 16,0    |
|                           |                    |         |         |
|                           |                    |         |         |