

panel mounting socket outlet, angled - flange 68x62,  
fixing centers 47x47



| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 12732  |
| EAN                       | 4024941127325                                      |
| Product category          | Panel mounting socket outlet Quick-Connect, angled |
| Current                   | 16A  |
| Number of poles           | 3p   |
| Arrangement of phases     | 2P+PE  |
| Position of earth contact | 6 h  |
| Voltage                   | 200 - 250V~  |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50/60Hz  |
| Protection degree              | IP44   |
| Colour code                    | blue RAL 5015  |
| Colour of appliance            | Hinged lid blue RAL 5015, Enclosure grey RAL 7035                |
| Connection design              | screwless spring terminals with Kontex-Kontakt                   |
| Maximum conductor size         | 4,0 qmm  |
| Cable entry                    | other  |
| Height                         | 75mm   |
| Width                          | 62mm   |
| Depth                          | 90mm   |
| Flange size vertical in mm     | 68mm   |
| Flange size horizontal in mm   | 62mm   |
| Drill hole dist. vertical mm   | 47mm   |
| Drill hole dist. horizontal mm | 47mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 20° |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.106 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941127325    |
| Length         | 90 mm            |
| Width          | 62 mm            |
| Height         | 75 mm            |
| Weight         | 0.107 kg         |
| Volume         | 418.5 ccm        |
| Packaging      | Carton           |
| Content amount | 10 ST            |
| EAN            | 4024941820769    |
| Length         | 207 mm           |
| Width          | 162 mm           |
| Height         | 142 mm           |
| Weight         | 1.16 kg          |
| Volume         | 3,750 ccm        |



4 MB 111

| Ampere                     | 16   | 16   | 16   |  |  |  |
|----------------------------|------|------|------|--|--|--|
| Polzahl                    | 3    | 4    | 5    |  |  |  |
| a                          | 68,0 | 87,0 | 87,0 |  |  |  |
| b                          | 62,0 | 71,0 | 71,0 |  |  |  |
| c                          | 47,0 | 70,0 | 70,0 |  |  |  |
| d                          | 47,0 | 52,0 | 52,0 |  |  |  |
| e Ø                        | 5,5  | 5,5  | 5,5  |  |  |  |
| f                          | 8,0  | 5,5  | 5,5  |  |  |  |
| h                          | 46,0 | 46,0 | 46,0 |  |  |  |
| i                          | 50,0 | 54,0 | 54,0 |  |  |  |
| k                          | -    | 9,5  | 9,5  |  |  |  |
| l                          | 56,0 | 65,0 | 72,0 |  |  |  |
| m                          | 51,0 | 58,0 | 64,0 |  |  |  |
| α                          | 20°  | 20°  | 20°  |  |  |  |
| Leiter mm <sup>2</sup> min | 1,5  | 1,5  | 1,5  |  |  |  |
| Leiter mm <sup>2</sup> max | 4    | 4    | 4    |  |  |  |