

Han 10B-asg2-K-M25



| Part number | 19 30 010 0266 |
|--------------------|-------------------------------------|
| Specification | Han 10B-asg2-K-M25 |
| HARTING eCatalogue | https://b2b.harting.com/19300100266 |

Identification

| Category | Hoods/Housings | |
|---------------------------------|---------------------------|--|
| Series of hoods/housings Han® B | | |
| Type of hood/housing | Surface mounted housing | |
| Description of hood/ housing | With thermo-plastic cover | |
| Туре | High construction | |

Version

| Locking type | Double locking lever (on the hood) |
|----------------------|---|
| Size | 10 B |
| Version | Side entry |
| Cable entry | 2x M25 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-----------------------------|----------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |



Material properties

| REACH ANNEX XIV substances | No |
|----------------------------|----|
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL | |
|-----------|--------|--|
|-----------|--------|--|

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 373.8 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |