

Phoenix								
Tragschiene - DIN Rail TS 15	X	X						
Tragschiene - DIN Rail TS 35			X	X	X	X	X	X
MUT: Spannung - Voltage (V)	500	500						
MUT: Strom - Current (A)	24	32						
UT: Spannung - Voltage (V)			1000	1000	1000	1000	1000	1000
UT: Strom - Current (A)			24	32	41	57	76	125
ST: Spannung - Voltage (V)			800	800	1000	1000	1000	1000
ST: Strom - Current (A)			24	32	41	57	76	125
Nennquerschnitt - Nom. cross section (mm ²)	2,5	4	2,5	4	6	10	16	35
Klemmenbreite - Terminal width (mm)	5,2	6,2	5,2	6,2	8,2	10,2	12,2	16
Klemmentyp - Terminal type Gehäusetyyp - Type	MUT 2,5	MUT 4	UT/ST 2,5	UT/ST 4	UT/ST 6	UT/ST 10	UT/ST 16	UT/ST 35
01.05 05 03								
01.06 06 03								
01.06 10 03								
01.06 12 00								
01.06 15 03								
01.06 19 00								
01.06 19 03								
01.08 08 06	6	5						
01.08 13 06	12	9						
01.08 18 06	25	21						
01.08 25 05	40	33						
01.10 10 08	11	9	11	9	7			
01.10 16 08	23	19	23	19	14			
01.10 20 08	30	25	30	25	19			
01.12 12 08			15	13	10	8	6	
01.12 12 09			15	13	10	8	6	
01.12 22 08			34	29	21	17	14	
01.12 22 09			34	29	21	17	14	
01.12 22 12			34	29	21	17	14	
01.12 36 08			61	51	39	31	26	
01.14 14 09			19	16	12	9	8	
01.14 20 09			30	25	19	15	13	
01.16 16 09			23	19	14	11	9	7
01.16 26 09			42	35	26	21	18	14
01.16 26 16			42	35	26	21	18	14
01.16 36 09			61	51	39	31	26	21
01.16 56 09			100	83	63	50	42	34
01.18 18 10			26	22	17	13	11	9
01.18 28 10			46	38	29	23	19	15
01.23 10 11			36	30	23			
01.23 20 11			62	52	38	15	13	10
01.23 20 18			62	52	38	15	13	10
01.23 28 11			92	76	58	46	19	15
01.23 33 11			110	92	70	56	23	19
01.23 33 18			110	92	70	56	23	19
01.23 40 11			138	116	86	70	29	23
01.23 40 18			138	116	86	70	29	23
01.23 40 23			138	116	86	70	29	23
01.23 60 11			214	180	136	54	45	36
01.31 40 11			210	174	132	70	58	23
01.31 40 14			210	174	132	70	58	23
01.31 40 18			210	174	132	70	58	23
01.31 40 23			210	174	132	70	58	23
01.31 60 11			321	270	204	108	90	36
01.31 60 18			321	270	204	108	90	36
01.60 60 20			428	360	204	162	135	108



Weidmüller												
Tragschiene - DIN Rail TS 15				X	X	X						
Tragschiene - DIN Rail TS 35							X	X	X	X	X	X
Spannung - Voltage (V)	400	400	400	250	250	400	800	800	800	1000	1000	1000
Strom - Current (A)	32	32	32	17,5	24	32	24	32	41	57	76	125
Nennquerschnitt - Nom. cross section (mm²)	4	4	4	1,5	2,5	4	2,5	4	6	10	16	35
Klemmenbreite - Terminal width (mm)	38	52	92	5,1	5,1	6,1	5,1	6,1	7,9	9,9	11,9	16
Klemmentyp - Terminal type Gehäusotyp - Type	BK 4 (4-pole)	BK 6 (6-pole)	BK 12 (12-pole)	AKZ 1,5	AKZ 2,5	AKZ 4	WDU 2,5	WDU 4	WDU 6	WDU 10	WDU 16	WDU 35
01.05 05 03												
01.06 06 03	1											
01.06 10 03		1										
01.06 15 03			1									
01.06 19 03			1									
01.08 08 06				4	4	3						
01.08 13 06				14	14	11						
01.08 18 06				24	23	20						
01.08 25 05				38	38	32						
01.10 10 08				9	9	7						
01.10 16 08				21	20	17						
01.10 20 08				28	28	24						
01.12 12 08				13	12	10	13	11	8			
01.12 12 09				13	12	10	13	11	8	6		
01.12 22 08				32	32	27	33	27	21	16		
01.12 22 09				32	32	27	33	27	21	16		
01.12 22 12				32	32	27	33	27	21	16		
01.12 36 08				59	59	49	61	50	38	30		
01.14 14 09				16	16	14	16	13	10	8		
01.14 20 09				28	28	23	28	23	17	14		
01.16 16 09				20	20	17	20	17	13	10		
01.16 26 09				40	39	33	40	33	25	20		
01.16 36 09				59	59	49	61	50	38	30		
01.16 56 09				98	98	82	100	84	63	50		
01.18 18 10				24	24	20	24	20	15	12	10	
01.18 28 10				43	43	36	44	37	28	22	18	
01.23 10 11				34	33	28						
01.23 20 11				56	56	46	56	46	36	14	11	8
01.23 20 18				56	56	46	56	46	36	14	11	8
01.23 28 11				86	86	72	88	72	56	44	18	12
01.23 33 11				106	106	88	108	90	68	54	22	15
01.23 33 18				106	106	88	108	90	68	54	22	15
01.23 40 11				132	132	110	136	114	86	68	29	19
01.23 40 18				132	132	110	136	114	86	68	29	19
01.23 40 23				132	132	110	136	114	86	68	29	19
01.23 60 11				212	210	176	216	180	134	54	45	30
01.31 40 11				198	198	165	204	171	129	51	42	19
01.31 40 14				198	198	165	204	171	129	51	42	19
01.31 40 18				198	198	165	204	171	129	51	42	19
01.31 40 23				198	198	165	204	171	129	51	42	19
01.31 60 11				318	315	264	324	270	204	108	90	30
01.31 60 18				318	315	264	324	270	204	108	90	30
01.60 60 20				416	416	348	432	360	204	162	135	120
Feldgehäuse mit integr. Außenbefestigung												
01.06 12 00		1										
01.06 19 00			1									

