

**Miele**

The world  
of Miele Marine



## PDR 514 ROP [EL SOM]

Vented dryer, electrically heated

with M Select ROP residual moisture control, for marine applications.&nbsp;

- Drum volume 250 l, load capacity 14 kg
- Unique, gentle fabric care – honeycomb drum
- Greatest energy efficiency thanks to Air Recycling
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance
Front	Iron grey
Fascia color	Edelstahl
Load in kg	14
Load size with a load ratio of 1:23	10
Load size with a load ratio of 1:18	14
Load ratio	1:18
Drum volume in l	250
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	13
Specific energy consumption in kWh/kg	0.53
Programme duration in min.	24
Tested operating hours	20000
<b>Controls</b>	
Control system	M Select
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Control panel with easy-to-understand symbols	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3 AC 400V 50/60HZ
Electric heater rating in kW	13.5
Total connected load in kW	14.1
Fuse rating in A	25
<b>Possible voltage variant 1</b>	
Electrical connection	3 AC 400V 60 HZ
Heater rating in kW	13.5
Total connected load in kW	14.1
Fuse rating in A	25

PDR 514 ROP [EL SOM]

Vented dryer, electrically heated

with M Select ROP residual moisture control, for marine applications.&nbsp;

<b>Dimensions and weight</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	852
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	938
Net weight in kg	160.4
Gross weight in kg	172
<b>Emissions data</b>	
Heat dissipation into the room in MJ/h	3.9
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•
<b>Test certificate</b>	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•

# Miele

**Miele & Cie. KG**

Carl-Miele-Straße 29  
33332 Gütersloh  
Germany  
Tel. +49 5241 89-0  
[www.miele-marine.com](http://www.miele-marine.com)

**International Service Contacts**

Americas: +1 609419 4376  
Australia, Asia, Oceania: +61 3 9764 7880  
Europe, Africa, Middle East: +049 5241 89 566 877

Email: [service@miele-marine.com](mailto:service@miele-marine.com)