The world of Miele Marine





PDR 914 [EL SOM]

Vented dryer, electrically heated with programmable M Touch Pro controls, for marine applications.

Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load in kg	14
Load size with a load ratio of 1:23	10
Load size with a load ratio of 1:18	14
Load ratio	1:18
Drum volume in I	250
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Maximum evaporation capacity in I/hour	13.3
Specific energy consumption in kWh/kg	0.51
Programme duration in min.	24
Tested operating hours	20000
Controls	
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	3 AC 400V 50/60HZ
Electric heater rating in kW	13.5
Total connected load in kW	14.1

25

- Drum volume 250 I 250 I, load capacity 14 kg
- Unique, gentle fabric care honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics
 - PerfectDry
- Connected for the future using LAN and WiFi

Fuse rating in A



PDR 914 [EL SOM]

Vented dryer, electrically heated with programmable M Touch Pro controls, for marine applications.

Dimensions and weight	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	852
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	938
Net weight in kg	160.4
Gross weight in kg	172
Emissions data	2.0
Heat dissipation into the room in MJ/h Features	3.9
Intelligent drum reversal	•
Axial airflow	
	- -
Large-surface fluff filter	- <u>-</u>
PerfectDry	_ -
SoftLift drum ribs	_ •
AirRecycling Flex	
Communication slot	
	<u>•</u>
Emergency switch-off	
Machine-independent accessories	•
Connection options	
Payment system (optional)	
Optical interface for service access	
Peak load cut-out/energy management (optional)	
Connector Box	
LAN/WiFi module (optional)	•
Capacities	
Respirator masks [number]	_ 8
Overalls [number]	
Over jackets [number]	
Synthetic duvets [number]	_ <u>1</u>
Synthetic pillows [number]	2
Down duvets [number]	_ 1
Down pillows [number]	2
Cloths, 22 g [number]	255
Cotton mops, 40 cm [number]	53
Cotton mops, 50 cm [number]	45
Microfibre mops, 40 cm [number]	83
Microfibre mops, 50 cm [number]	59
Summer horse blankets [number]	2



PDR 914 [EL SOM]

Vented dryer, electrically heated with programmable M Touch Pro controls, for marine applications.

Test certificate	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•



Miele & Cie. KG

Carl-Miele-Straße 29 33332 Gütersloh Germany Tel. +49 5241 89-0 www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376 Australia, Asia, Oceania: +61 3 9764 7880 Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com