

**Miele**

The world  
of Miele Marine



PDR 918 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.&nbsp;

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load in kg	18
Load size with a load ratio of 1:23	13
Load size with a load ratio of 1:18	18
Load ratio	1:18
Drum volume in l	325
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	18,5
Specific energy consumption in kWh/kg	0,52
Programme duration in min.	23
Tested operating hours	20000
<b>Controls</b>	
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3 AC 230V 50/60HZ
Electric heater rating in kW	18
Total connected load in kW	18,6
Fuse rating in A	50

- Drum volume 325 l, load capacity 18 kg
- Unique, gentle fabric care – honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

PDR 918 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.&nbsp;

<b>Dimensions and weight</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1415
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1925
Net weight in kg	169.5
Gross weight in kg	183
<b>Emissions data</b>	
Heat dissipation into the room in MJ/h	4
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling Flex	•
Communication slot	•
	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•
<b>Capacities</b>	
Respirator masks [number]	12
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	1
Down pillows [number]	3
Cloths, 22&nbsp;g [number]	320
Summer horse blankets [number]	3
<b>Test certificate</b>	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

# Miele

**Miele & Cie. KG**

Carl-Miele-Straße 29  
33332 Gütersloh  
Germany  
Tel. +49 5241 89-0  
[www.miele-marine.com](http://www.miele-marine.com)

**International Service Contacts**

Americas: +1 609419 4376  
Australia, Asia, Oceania: +61 3 9764 7880  
Europe, Africa, Middle East: +049 5241 89 566 877

Email: [service@miele-marine.com](mailto:service@miele-marine.com)