

# The world of Miele Marine





#### PDR 918 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

Construction type	Front loader
	Performance Plus
Range Front	Stainless steel
Load in kg	18
Load size with a load ratio of 1:23	13
Load size with a load ratio of 1:18	18
Load ratio	1:18
Drum volume in I	325
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Maximum evaporation capacity in I/hour	18.5
Specific energy consumption in kWh/kg	0.52
Programme duration in min.	23
Tested operating hours	20000
Controls	
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	3 AC 400V 50/60HZ
Electric heater rating in kW	18
Total connected load in kW	18.6
Fuse rating in A	35

- Drum volume 325 I 325 I, load capacity 18 kg
- Unique, gentle fabric care honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi



## PDR 918 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

Dimensions and weight	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1035
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1125
Net weight in kg	173.5
Gross weight in kg	187
Emissions data	
Heat dissipation into the room in MJ/h	4.5
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling Flex	•
Communication slot	•
	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•
Capacities	
Respirator masks [number]	12
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	1
Down pillows [number]	3
Cloths, 22 g [number]	320
Cotton mops, 40 cm [number]	68
Cotton mops, 50 cm [number]	59
Microfibre mops, 40 cm [number]	108
	76
Microfibre mops, 50 cm [number]	70



## PDR 918 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

Test certificate	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•

Complies with Machinery Directive 2006/42/EC



Miele & Cie. KG Carl-Miele-Straße 29 33332 Gütersloh Germany Tel. +49 5241 89-0 www.miele-marine.com

#### International Service Contacts

Americas: Australia, Asia, Oceania: Europe, Africa, Middle East: +049 5241 89 566 877

+1 609419 4376 +61 3 9764 7880

Email: service@miele-marine.com