

Miele

The world
of Miele Marine



PDR 928 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

- Drum volume 500 l, load capacity 28 kg
- Unique, gentle fabric care – honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

| Construction type and version | |
|--|------------------------------|
| Construction type | Front loader |
| Range | Performance Plus |
| Front | Stainless steel |
| Load in kg | 28 |
| Load size with a load ratio of 1:23 | 20 |
| Load size with a load ratio of 1:18 | 28 |
| Load ratio | 1:18 |
| Drum volume in l | 500 |
| Drying system | Vented |
| Door opening [Ø] in mm | 520 |
| Door opening angle in degrees | 180 |
| Door hinge | left |
| Convertible door hinging | • |
| Stainless steel honeycomb drum | • |
| Application | |
| Suitable for offshore use | • |
| Suitable for marine use | • |
| Performance data | |
| Maximum evaporation capacity in l/hour | 27.2 |
| Specific energy consumption in kWh/kg | 0.51 |
| Programme duration in min. | 24 |
| Tested operating hours | 20000 |
| Controls | |
| Programmability | programmable |
| User interface | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Selectable display languages | • |
| Standard electrical connection | |
| Heating type | Electrical |
| Electrical connection | 3 AC 400V 50/60HZ |
| Electric heater rating in kW | 27 |
| Total connected load in kW | 28.2 |
| Fuse rating in A | 50 |

PDR 928 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

| Dimensions and weight | |
|--|-------|
| External dimensions, height in mm | 1640 |
| External dimensions, width in mm | 1206 |
| External dimensions, depth in mm | 1019 |
| External dimensions, gross height in mm | 1766 |
| External dimensions, gross width in mm | 1390 |
| External dimensions, gross depth in mm | 1108 |
| Net weight in kg | 243.3 |
| Gross weight in kg | 258 |
| Emissions data | |
| Heat dissipation into the room in MJ/h | 3.3 |
| Features | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Large-surface fluff filter | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| AirRecycling Flex | • |
| Communication slot | • |
| | • |
| Emergency switch-off | • |
| Machine-independent accessories | • |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Peak load cut-out/energy management (optional) | • |
| Connector Box | • |
| LAN/WiFi module (optional) | • |
| Capacities | |
| Respirator masks [number] | 12 |
| Overalls [number] | 3 |
| Over jackets [number] | 5 |
| Synthetic duvets [number] | 2 |
| Synthetic pillows [number] | 5 |
| Down duvets [number] | 2 |
| Down pillows [number] | 5 |
| Cloths, 22 g [number] | 500 |
| Cotton mops, 40 cm [number] | 105 |
| Cotton mops, 50 cm [number] | 91 |
| Microfibre mops, 40 cm [number] | 167 |
| Microfibre mops, 50 cm [number] | 118 |
| Summer horse blankets [number] | 3 |

PDR 928 [EL SOM]

Vented dryer, electrically heated

with programmable M Touch Pro controls, for marine applications.

| Test certificate | |
|--|---|
| CE | • |
| VDE | • |
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| EAC | • |
| Complies with Machinery Directive 2006/42/EC | • |

Miele

Miele & Cie. KG

Carl-Miele-Straße 29
33332 Gütersloh
Germany
Tel. +49 5241 89-0
www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376
Australia, Asia, Oceania: +61 3 9764 7880
Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com