

**Miele**



PT 7186 Vario XL [EL SOM - 3AC 440V 60Hz]

Vented dryer, electrically heated

Specially designed for marine requirements.



- Drum volume 180 l, load capacity 9.0kg
- Large programme variety - application-specific drying programmes
- Precision drying of all fabrics – PerfectDry
- Unique, gentle fabric care – honeycomb drum
- Easy operation - viewing window and large-surface filter

EAN: 4002516236825 / Article number : 527186X2SOM / Material number: 11331680

<b>Construction type and version</b>	
Construction type	Front loader
Range	OctoPlus
Front	Stainless steel
Maximum load size in kg	9.0
Load ratio	1:20
Drum volume in l	180
Drying system	Vented
Door opening [Ø] in mm	440
Door opening angle in degrees	180
Door hinge	left
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	8.1
Programme duration in min.	41
<b>Controls</b>	
Control system	Profitronic L Vario
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3 AC 440V 60HZ
Electric heater rating in kW	7.94
Total connected load in kW	8.50
Fuse rating in A	16
<b>Dimensions and weight</b>	
External dimensions, net height in mm	1,020
External dimensions, net width in mm	700
External dimensions, net depth in mm	763
External dimensions, gross height in mm	1,215
External dimensions, gross width in mm	760
External dimensions, gross depth in mm	820
Net weight in kg	77
Gross weight in kg	88
Maximum floor loading in N	1020

PT 7186 Vario XL [EL SOM - 3AC 440V 60Hz]

Vented dryer, electrically heated

Specially designed for marine requirements.



<b>Emissions data</b>	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.62
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drying basket (optional)	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	89
<b>Connection options</b>	
Payment system	•
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
<b>Capacities</b>	
Respirator masks [number]	4
Overalls [number]	1
Over jackets [number]	1-2
Synthetic duvets [number]	1
Synthetic pillows [number]	1-2
Down duvets [number]	1
Down pillows [number]	1-2
Cloths, 22 g [number]	182
Cotton mops, 40 cm [number]	42
Cotton mops, 50 cm [number]	36
Microfibre mops, 40 cm [number]	66
Microfibre mops, 50 cm [number]	47
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.