

**Miele**

The world  
of Miele Marine



## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Model and design</b>	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Maximum load with a load ratio of 1:9 in kg	12
Load ratio	1:9
Load in kg	12
Drum volume in l	110
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•

- Drum volume 110 l, maximum load capacity 12 kg
- Top cleaning & consumption values – innovative Miele technology
- Ideal operation thanks to colour touch display – M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Performance data</b>	
Specific water consumption for cold water connection in l/kg	6.2
Specific energy consumption for cold water connection in kWh/kg	0.14
Specific water consumption for hot water connection in l/kg	5.9
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in l	74.4
	142.2
Energy consumption with cold water connection in kW	1.68
	2.5
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in l	70.8
	139.9
Energy consumption with hot water connection in kW	0.72
	1
Programme duration in minutes with cold water and hot water connection	42
Water consumption in ECO programme with cold water connection in l	69.6
Energy consumption in ECO programme with cold water connection in ECO programme	1.2
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in l	68.4
Energy consumption in ECO programme with hot water connection in ECO programme	0.36
Programme duration in minutes with cold water and hot water connection in ECO programme	31
Mop programme duration in min.	54
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	1150
g factor	458
Tested operating hours	30000
<b>Controls</b>	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Option to enter weight prior to start of programme	•
<b>Standard and target group Programmes</b>	
Basic programmes	•

## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Dispensing</b>	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	9
Total connected load in kW	9.6
Fuse rating in A	16
<b>Possible voltage variant 1</b>	
Electrical connection	3N AC 400V 60HZ
Heater rating in kW	9
Total connected load in kW	9.6
Fuse rating in A	16
<b>Water connection/drainage</b>	
Cold water [number]	3&nbsp;x&nbsp;1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water [number]	2 1/2" w/ 3/4" threaded union.
Dump valve	DN 70
<b>Dimensions and weight</b>	
External dimensions, height in mm	1350
External dimensions, width in mm	799
External dimensions, depth in mm	924
External dimensions, gross height in mm	1480
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1130
Net weight in kg	271
Gross weight in kg	290
Maximum floor loading in N	4402
<b>Emissions data</b>	
Heat dissipation into the room in MJ/h	6.48

## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Features</b>	
Patented pre-spin	•
Cloth reprocessing	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Weighing plinth (optional)	•
Programme selection via colour frame	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	91
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Water recovery (optional)	•
LAN	•
WiFi	•
Connector Box	•
<b>Capacities</b>	
Respirator masks [number]	10
Helmets [number]	3
Overalls [number]	2
Over jackets [number]	3
Chemical protection suits [number]	1
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22&nbsp;g [number]	289
Cotton mops, 40&nbsp;cm / 190&nbsp;g [number]	64
Cotton mops, 50&nbsp;cm / 220&nbsp;g [number]	56
Microfibre mops, 40&nbsp;cm / 120&nbsp;g [number]	100
Microfibre mops, 50&nbsp;cm / 170&nbsp;g [number]	72
Mops, office, 100&nbsp;g [quantity]	120
Mops, stairway, 150&nbsp;g [quantity]	80
Summer horse blankets [number]	2

PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

Test certificate	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•

## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Model and design</b>	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Maximum load with a load ratio of 1:9 in kg	12
Load ratio	1:9
Load in kg	12
Drum volume in l	110
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•

- Drum volume 110 l, maximum load capacity 12 kg
- Top cleaning & consumption values – innovative Miele technology
- Ideal operation thanks to colour touch display – M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Performance data</b>	
Specific water consumption for cold water connection in l/kg	6.2
Specific energy consumption for cold water connection in kWh/kg	0.14
Specific water consumption for hot water connection in l/kg	5.9
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in l	74.4
	142.2
Energy consumption with cold water connection in kW	1.68
	2.5
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in l	70.8
	139.9
Energy consumption with hot water connection in kW	0.72
	1
Programme duration in minutes with cold water and hot water connection	42
Water consumption in ECO programme with cold water connection in l	69.6
Energy consumption in ECO programme with cold water connection in ECO programme	1.2
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in l	68.4
Energy consumption in ECO programme with hot water connection in ECO programme	0.36
Programme duration in minutes with cold water and hot water connection in ECO programme	31
Mop programme duration in min.	54
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	1150
g factor	458
Tested operating hours	30000
<b>Controls</b>	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Option to enter weight prior to start of programme	•
<b>Standard and target group Programmes</b>	
Basic programmes	•



## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Dispensing</b>	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	9
Total connected load in kW	9.6
Fuse rating in A	16
<b>Possible voltage variant 1</b>	
Electrical connection	3N AC 400V 60HZ
Heater rating in kW	9
Total connected load in kW	9.6
Fuse rating in A	16
<b>Water connection/drainage</b>	
Cold water [number]	3&nbsp;x&nbsp;1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water [number]	2 1/2" w/ 3/4" threaded union.
Dump valve	DN 70
<b>Dimensions and weight</b>	
External dimensions, height in mm	1350
External dimensions, width in mm	799
External dimensions, depth in mm	924
External dimensions, gross height in mm	1480
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1130
Net weight in kg	271
Gross weight in kg	290
Maximum floor loading in N	4402
<b>Emissions data</b>	
Heat dissipation into the room in MJ/h	6.48

## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

<b>Features</b>	
Patented pre-spin	•
Cloth reprocessing	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Weighing plinth (optional)	•
Programme selection via colour frame	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	91
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Water recovery (optional)	•
LAN	•
WiFi	•
Connector Box	•
<b>Capacities</b>	
Respirator masks [number]	10
Helmets [number]	3
Overalls [number]	2
Over jackets [number]	3
Chemical protection suits [number]	1
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22&nbsp;g [number]	289
Cotton mops, 40&nbsp;cm / 190&nbsp;g [number]	64
Cotton mops, 50&nbsp;cm / 220&nbsp;g [number]	56
Microfibre mops, 40&nbsp;cm / 120&nbsp;g [number]	100
Microfibre mops, 50&nbsp;cm / 170&nbsp;g [number]	72
Mops, office, 100&nbsp;g [quantity]	120
Mops, stairway, 150&nbsp;g [quantity]	80
Summer horse blankets [number]	2

PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M&nbsp;Touch&nbsp;Pro&nbsp;Plus freely programmable, for marine use.

Test certificate	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•

# Miele

**Miele & Cie. KG**

Carl-Miele-Straße 29  
33332 Gütersloh  
Germany  
Tel. +49 5241 89-0  
[www.miele-marine.com](http://www.miele-marine.com)

**International Service Contacts**

Americas: +1 609419 4376  
Australia, Asia, Oceania: +61 3 9764 7880  
Europe, Africa, Middle East: +049 5241 89 566 877

Email: [service@miele-marine.com](mailto:service@miele-marine.com)