



Product Features

UAE-jack, double, flush mounting, with LSA-contacts, 2x8 way, with 2x8 LSA-contacts, with plastic mounting brackets, with spreading claws, pure white (similar RAL 9010)

- openings for 6- and 8-way plugs (RJ12 and RJ45)
- suitable for RJ11/12 without additional reducing adapters
- plastic mounting brackets
- with spreading claws
- jacks positioned downward sloped
- screw terminals for wires up to 1mm Ø, 2 wires at each contact
- LSA-terminals for one wire 0,4-0,63 mm Ø, AW 26-22, max. number of connections > 50-times
- gold plated contacts
- voltage: 125 V
- operation current: 1 A bei 50° C
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- contact withstand: < 20 mO
- according to the following standards:
- TIA/EIA-568-B.2-2001, Cat. 3
- life (insertions and withdrawals): > 2500 cycles
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten u.a.)

Features

General	
Centre plate	Yes
Design	jack
Design capability	Yes
Classification	Cat.3
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921061664
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes
trunking installation	Yes

Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	30
Net weight piece kg	0,042
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,51
Packaging unit Width mm	138
Packaging unit Height mm	166
Packaging unit Depth mm	83
References	
Accessories	10010001, 10010051, 10010055, 10010070, 13510002, 13510003, 13510052, 13510053, 13510503, 13511503, 681072
Similar article	13010247, 13011112

