

Han PushPull RJ45 Genderchanger



Part number	09 35 221 0501
Specification	Han PushPull RJ45 Genderchanger
HARTING eCatalogue	https://b2b.harting.com/09352210501
Features	Intuitive locking mechanism

Identification

Category	Connector
Series	Han® PushPull
Identification	RJ45
Element	Gender changer
Specification	AIDA compliant

Version

Locking type	PushPull
Fixing	Wall mountable with 4 screws type M5

Technical characteristics

Rated current	1.75 A
Rated voltage	50 V
Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 when mated IP67 when mated
Transmission characteristics	Cat. 6 Class E up to 250 MHz

Material properties

Material (hood/housing)	Aluminium
Surface (hood/housing)	Anodised
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No



Pushing Performance

Material properties

REACH SVHC substances	No
-----------------------	----

Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 60603-7 Mating face
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
PROFINET	Yes

Commercial data

Packaging size	1
Net weight	124.25 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440307 I/O connector