


ARUN-RE LED recessed spot, 2-x

Article no. 12618173

Light.
For Generations.**Tender**

LED recessed spot, 2-x, Rectangular. Toolless ceiling installation by installation springs. Ceiling cut-out L x W 83 x 172 mm, Installation depth 95 mm, Length 92 mm, Width 184 mm, Weight 0,565 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a Without cover cover. Luminous flux 2.600 lm, Power 2 x 12,2 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium / Plastic, Colour: White structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20, .For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Product Benefits

- Recessed spot in rectangular shape made of solid aluminum.
- Ceiling cutout 174 x 83 mm, width 92 mm, length 184 mm, installation depth 95 mm, luminous flux 2 x 1,300 lm, IP20.
- Pivoting range 30°, rotating range 355°.
- Dimmable when using a suitable converter.
- In the same surface structure and in the same color also available in round, square and oval versions.

ARUN-RE LED recessed spot, 2-x

Article no. 12618173

Light.
For Generations.

Article data	
Article no.	12618173
GTIN	4251433920229
Series name	ARUN-RE
Short description	LED recessed spot, 2-x
Material	Aluminium / Plastic
Colour	White
Type of surface	Structure
Shape	Rectangular
Built-in width	172 mm
Built-in length	83 mm
Installation depth	95 mm
Length	92 mm
Width	184 mm
Height	2 mm
Weight	0.565 kg

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	2,600 lm
System efficiency	213 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Reflektorfarbe	silver
Beam angle	29°
Light sharing	Symmetric

Operating technology of the luminaire	
Voltage type	DC
Current	350 mA
Lamp	LED
Protection class	III
Degree of protection	IP20
Dimmable	Depending on type of control gear
Control	Depending on driver
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Rotable and pivoted
Swivel angle	30°
Rotation angle	355°
Max. ceiling thickness	15 mm
Further references	No cover with thermal insulation material
Material cover	Without cover

ARUN-RE LED recessed spot, 2-x

Article no. 12618173

Light.
For Generations.

Packing data	
Gross weight	0.693 kg
Length of packaging	135 mm
Packaging width	135 mm
Packaging height	115 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>